

Bay Area Air Quality Management District

939 Ellis Street
San Francisco, CA 94109
(415) 771-6000

Proposed

MAJOR FACILITY REVIEW PERMIT

Issued To:

Allied Waste Industries, Inc.
Facility #A4618

Facility Address:

901 Bailey Road
Pittsburg, CA 94565

Mailing Address:

901 Bailey Road
Pittsburg, CA 94565

Responsible Official

Michael Caprio, District Manager
925-458-9800

Facility Contact

Norm Christensen, General Manager
925-458-9800

Type of Facility: Municipal Solid Waste Landfill
Primary SIC: 4953
Product: Class II Solid Waste Disposal

BAAQMD Permit Division Contact:
Carol S. Allen

ISSUED BY THE BAY AREA AIR QUALITY MANAGEMENT DISTRICT

William C. Norton, Executive Officer/Air Pollution Control Officer

Date

TABLE OF CONTENTS

I. STANDARD CONDITIONS 3

II. EQUIPMENT 7

III. GENERALLY APPLICABLE REQUIREMENTS..... 8

IV. SOURCE-SPECIFIC APPLICABLE REQUIREMENTS 10

V. SCHEDULE OF COMPLIANCE..... 33

VI. PERMIT CONDITIONS 34

VII. APPLICABLE LIMITS AND COMPLIANCE MONITORING REQUIREMENTS 52

VIII. TEST METHODS..... 72

IX. PERMIT SHIELD..... 76

X. REVISION HISTORY..... 77

XI. GLOSSARY 79

XII. APPLICABLE STATE IMPLEMENTATION PLAN..... 86

I. STANDARD CONDITIONS

A. Administrative Requirements

The permit holder shall comply with all applicable requirements in the following regulations:

BAAQMD Regulation 1 - General Provisions and Definitions

(as amended by the District Board on 5/2/01);

SIP Regulation 1 - General Provisions and Definitions

(as approved by EPA through [8/27/99](#)[6/28/99](#));

BAAQMD Regulation 2, Rule 1 - Permits, General Requirements

(as amended by the District Board on 8/1/01);

SIP Regulation 2, Rule 1 - Permits, General Requirements

(as approved by EPA through [2/25/99](#)[1/26/99](#));

BAAQMD Regulation 2, Rule 2 - Permits, New Source Review

(as amended by the District Board on 5/17/00);

SIP Regulation 2, Rule 2 - Permits, New Source Review and Prevention of Significant Deterioration

(as approved by EPA through [2/25/99](#)[1/26/99](#));

BAAQMD Regulation 2, Rule 4 - Permits, Emissions Banking

(as amended by the District Board on 5/17/00);

SIP Regulation 2, Rule 4 - Permits, Emissions Banking

(as approved by EPA through [2/25/99](#)[1/26/99](#)); and

BAAQMD Regulation 2, Rule 6 - Permits, Major Facility Review

(as amended by the District Board on [5/2/01](#)[4/16/03](#)).

B. Conditions to Implement Regulation 2, Rule 6, Major Facility Review

1. This Major Facility Review Permit was issued on September 20, 2001 and expires on August 31, 2006. The permit holder shall submit a complete application for renewal of this Major Facility Review Permit no later than February 28, 2006 and no earlier than August 31, 2005. **If a complete application for renewal has not been submitted in accordance with this deadline, the facility may not operate after August 31, 2006.** (Regulation 2-6-307, 404.2, & 409.6; MOP Volume II, Part 3, §4.2)
2. The permit holder shall comply with all conditions of this permit. The permit consists of this document and all appendices. Any non-compliance with the terms and conditions of this permit will constitute a violation of the law and will be grounds for enforcement action; permit termination, revocation and re-issuance, or modification; or denial of a permit renewal application. (Regulation 2-6-307; MOP Volume II, Part 3, §4.11)
3. In the event any enforcement action is brought as a result of a violation of any term or condition of this permit, the fact that it would have been necessary for the permittee to halt or reduce the permitted activity in order to maintain compliance with such term or condition shall not be a defense to such enforcement action. (MOP Volume II, Part 3, §4.11)
4. This permit may be modified, revoked, reopened and reissued, or terminated for cause. (Regulation 2-6-307, 409.8, 415; MOP Volume II, Part 3, §4.11)
5. The filing of a request by the facility for a permit modification, revocation and re-

I. Standard Conditions

- issuance, or termination, or the filing of a notification of planned changes or anticipated non-compliance does not stay the applicability of any permit condition. (Regulation 2-6-409.7; MOP Volume II, Part 3, §4.11)
6. This permit does not convey any property rights of any sort, or any exclusive privilege. (Regulation 2-6-409.7; MOP Volume II, Part 3, §4.11)
 7. The permit holder shall supply within 30 days any information that the District requests in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. (Regulation 1-441, Regulation 2-6-409.4 & 501; MOP Volume II, Part 3, §4.11)
 8. Any records required to be maintained pursuant to this permit ~~which~~that the permittee considers to contain proprietary or trade secret information shall be prominently designated as such. Copies of any such proprietary or trade secret information which are provided to the District shall be maintained by the District in a locked confidential file, provided, however, that requests from the public for the review of any such information shall be handled in accordance with the District's procedures set forth in Section 11 of the District's Administrative Code. (Regulation 2-6-419; MOP Volume II, Part 3, §4.11)
 9. Proprietary or trade secret information provided to EPA will be subject to the requirements of 40 CFR Part 2, Subpart B - Public Information, Confidentiality of Business Information. (40 CFR Part 2)
 10. The emissions inventory submitted with the application for this Major Facility Review Permit is an estimate of actual emissions or the potential to emit for the time period stated and is included only as one means of determining applicable requirements for emission sources. It does not establish, or constitute a basis for establishing, any new emission limitations. (MOP Volume II, Part 3, §4.11)
 11. The responsible official shall certify all documents submitted by the facility pursuant to the major facility review permit. The certification shall state that based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete. The certifications shall be signed by a responsible official for the facility. (MOP Volume II, Part 3, §4.11)

C. Requirement to Pay Fees

The permit holder shall pay annual fees in accordance with District Regulation 3, including Schedule P. (Regulation 2-6-402 & 409.13, Regulation 3; MOP Volume II, Part 3, §4.12)

D. Inspection and Entry

Access to Facility: The permit holder shall provide reasonable access to the facility and equipment which is subject to this permit to the APCO and/or to his or her designee. (Regulation 1-440, Regulation 2-6-409.3; MOP Volume II, Part 3, §4.14)

E. Records

1. The permit holder must provide any information, records, and reports requested or specified by the APCO. (Regulation 1-441, Regulation 2-6-409.4)

I. Standard Conditions

2. Notwithstanding the specific wording in any requirement, all records for federally enforceable requirements shall be maintained for at least five years from the date of creation of the record. (Regulation 2-6-501, Regulation 3; MOP Volume II, Part 3, §4.7)

F. Monitoring Reports

Reports of all required monitoring must be submitted to the District at least once every six months, except where an applicable requirement specifies more frequent reporting. The first reporting period for this permit shall be September 20, 2001 to February 28, 2002. The report shall be submitted by March 31, 2002. Subsequent reports shall be for the following periods: March 1st through August 31st and September 1st through February 28th or 29th, and are due on the last day of the month after the end of the reporting period. All instances of non-compliance shall be clearly identified in these reports. The reports shall be certified by the responsible official as true, accurate, and complete. In addition, all instances of non-compliance with the permit shall be reported in writing to the District's Compliance and Enforcement Division within 10 calendar days of the discovery of the incident. Within 30 calendar days of the discovery of any incident of non-compliance, the facility shall submit a written report including the probable cause of non-compliance and any corrective or preventative actions. The reports shall be sent to the following address:

Director of Compliance and Enforcement
Bay Area Air Quality Management District
939 Ellis Street
San Francisco, CA 94109
Attn: Title V Reports

(Regulation 2-6-502, Regulation 3; MOP Volume II, Part 3, §4.7)

G. Compliance Certification

Compliance certifications shall be submitted annually by the responsible official of this facility to the Bay Area Air Quality Management District and to the Environmental Protection Agency. The certification period will be September 1st to August 31st. The certification shall be submitted by September 30th of each year. The certification must list each applicable requirement, the compliance status, whether compliance was continuous or intermittent, the method used to determine compliance, and any other specific information required by the permit. The permit holder may satisfy this requirement through submittal of District-generated Compliance Certification forms. The certification should be directed to the District's Compliance and Enforcement Division at the address above, and a copy of the certification should be sent to the Environmental Protection Agency at the following address:

Director of the Air Division
USEPA, Region IX
75 Hawthorne Street
San Francisco, CA 94105
Attention: Air-3

I. Standard Conditions

(MOP Volume II, Part 3, §4.5 and 4.15)

H. Emergency Provisions

1. The permit holder may seek relief from enforcement action in the event of a breakdown, as defined by Regulation 1-208 of the District's Rules and Regulations, by following the procedures contained in Regulations 1-431 and 1-432. The District will thereafter determine whether breakdown relief will be granted in accordance with Regulation 1-433. (MOP Volume II, Part 3, §4.8)
2. The permit holder may seek relief from enforcement action for a violation of any of the terms and conditions of this permit by applying to the District's Hearing Board for a variance pursuant to Health and Safety Code Section 42350. The Hearing Board will determine after notice and hearing whether variance relief should be granted in accordance with the procedures and standards set forth in Health and Safety Code Section 42350 et seq. (MOP Volume II, Part 3, §4.8)
3. The granting by the District of breakdown relief or the issuance by the Hearing Board of a variance will not provide relief from federal enforcement. (MOP Volume II, Part 3, §4.8)

I. Severability

In the event that any provision of this permit is invalidated by a court or tribunal of competent jurisdiction, or by the Administrator of the EPA, all remaining portions of the permit shall remain in full force and effect. (Regulation 2-6-409.5; MOP Volume II, Part 3, §4.10)

J. Miscellaneous Conditions

1. The maximum capacity for each source as shown in Table II-A is the maximum allowable capacity. Exceedance of the maximum allowable capacity for any source is a violation of Regulation 2, Rule 1, Section 301. (Regulation 2-1-301)

II. EQUIPMENT

Table II A - Permitted Sources

Each of the following sources has been issued a permit to operate pursuant to the requirements of BAAQMD Regulation 2, Permits. The capacities in this table are the maximum allowable capacities for each source, pursuant to Standard Condition I.J. and Regulation 2-1-301.

S-#	Description	Make or Type	Model	Capacity
1	Keller Canyon Landfill with Active Gas Collection System:	Class II Disposal Operations (MSW, commercial, industrial, construction, designated, and special wastes)		Max. Design Capacity (waste and cover, excluding final cover) = 75 million yd ³ (57.3 million m ³) Max. Waste Acceptance Rate = 3500 tons/day Max. Cumulative Waste In-Place = 38.4 million tons (34.8 million Mg)
	Gas Collection Wells, Phase I Disposal Cell			42-50 vertical wells
2	Wipe Cleaning Operation	Mineral Spirits		100 Gallons/year
3	Yard and Green Waste Stockpiles	Yard and Green Waste		225 tons/day

Table II B – Abatement Devices

A-#	Description	Source(s) Controlled	Applicable Requirement	Operating Parameters	Limit or Efficiency
1	Enclosed Ground Flare, burning propane (during start-up only) and landfill gas 72.7 MMBtu/hr	S-1	BAAQMD 8-34-301.3 , See also Table IV-D	Minimum combustion zone temperature of: 1550 °F (3-hour average). See See also Table VII-D	Either 98% destruction of NMOC or < 30 ppmv of NMOC, as CH₄, at 3% O₂, dry. See also Table VII-D

III. GENERALLY APPLICABLE REQUIREMENTS

The permit holder shall comply with all applicable requirements, including those specified in the BAAQMD and SIP Rules and Regulations and other federal requirements cited below. These requirements apply in a general manner to the facility and/or to sources exempt from the requirement to obtain a District Permit to Operate. The District has determined that these requirements will not be violated under normal, routine operations, and that no additional periodic monitoring or reporting to demonstrate compliance is warranted. In cases where a requirement, in addition to being generally applicable, is also specifically applicable to one or more sources, the requirement and the source are also included in Section IV, Source-Specific Applicable Requirements, of this permit.

The dates in parentheses in the Title column identify the versions of the regulations being cited and are, as applicable:

1. BAAQMD regulation(s): The date(s) of adoption or most recent amendment of the regulation by the District Board of Directors
2. Any federal requirement, including a version of a District regulation that has been approved into the SIP: The most recent date of EPA approval of any portion of the rule, encompassing all actions on the rule through that date

The full language of SIP requirements is ~~included in Appendix A of this permit if the SIP requirement is different from the current BAAQMD requirement on EPA Region 9's website. The address is included at the end of this permit.~~

NOTE:

There are differences between the current BAAQMD rules and the version of the rules in the SIP. All sources must comply with both versions of the rule until US EPA has reviewed and approved the District's revision of the regulation.

Table III
Generally Applicable Requirements

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)
BAAQMD Regulation 1	General Provisions and Definitions (5/2/01)	N
SIP Regulation 1	General Provisions and Definitions (8/27/99 6/28/99)	Y ¹
BAAQMD Regulation 2, Rule 1	General Requirements (8/1/01)	N
BAAQMD 2-1-429	Federal Emissions Statement (6/7/95)	Y
SIP Regulation 2, Rule 1	General Requirements (8/27/99 1/26/99)	Y ¹
BAAQMD Regulation 5	Open Burning (11/2/94 3/6/02)	Y N
<u>SIP Regulation 5</u>	<u>Open Burning (9/4/98)</u>	<u>Y</u> ¹
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)	Y
BAAQMD Regulation 7	Odorous Substances (3/17/82)	N
BAAQMD Regulation 8, Rule 1	Organic Compounds - General Provisions (6/15/94)	Y
<u>BAAQMD Regulation 8, Rule 2</u>	<u>Organic Compounds – Miscellaneous Operations (6/15/94)</u>	<u>Y</u>

III. Generally Applicable Requirements

Table III
Generally Applicable Requirements

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)
BAAQMD Regulation 8, Rule 3	Organic Compounds - Architectural Coatings (4/4/98 11/21/01)	N
SIP Regulation 8, Rule 3	Organic Compounds - Architectural Coatings (2/18/98)	Y ¹
BAAQMD Regulation 8, Rule 4	Organic Compounds - General Solvent and Surface Coating Operations (10/16/02)	N
SIP Regulation 8, Rule 4	Organic Compounds - General Solvent and Surface Coating Operations (12/23/97)	Y ¹
BAAQMD Regulation 8, Rule 16	Organic Compounds – Solvent Cleaning Operations (9/16/98 10/16/02)	N
SIP Regulation 8, Rule 16	Organic Compounds – Solvent Cleaning Operations (12/9/94)	Y ¹
BAAQMD Regulation 8, Rule 40	Organic Compounds – Aeration of Contaminated Soil and Removal of Underground Storage Tanks (12/15/99)	Y
BAAQMD 8-40-116	Exemption, Small Volume	Y
BAAQMD 8-40-117	Exemption, Accidental Spills	Y
BAAQMD Regulation 8, Rule 49	Organic Compounds - Aerosol Paint Products (12/20/95)	N
SIP Regulation 8, Rule 49	Organic Compounds - Aerosol Paint Products (3/22/95)	Y ¹
BAAQMD Regulation 8, Rule 51	Organic Compounds - Adhesive and Sealant Products (4/17/98 7/17/02)	N
SIP Regulation 8, Rule 51	Organic Compounds - Adhesive and Sealant Products (2/26/02)	Y ¹
BAAQMD Regulation 11, Rule 1	Hazardous Pollutants – Lead (3/17/82)	N
SIP Regulation 11, Rule 1	Hazardous Pollutants – Lead (9/2/81)	Y ¹
BAAQMD Regulation 11, Rule 2	Hazardous Pollutants - Asbestos Demolition, Renovation and Manufacturing (10/7/98)	N
BAAQMD Regulation 11, Rule 14	Hazardous Pollutants - Asbestos Containing Serpentine (7/17/91)	N
BAAQMD Regulation 12, Rule 4	Miscellaneous Standards of Performance – Sandblasting (7/11/90)	N
SIP Regulation 12, Rule 4	Miscellaneous Standards of Performance – Sandblasting (9/2/81)	Y ¹
California Health and Safety Code Section 44300 et seq.	Air Toxics “Hot Spots” Information and Assessment Act of 1987	N

1. This section has been removed from BAAQMD Regulations because it has been superseded. Nevertheless, the source must comply with this regulation until US EPA has reviewed and approved (or disapproved) the District’s revision of the regulation.

IV. SOURCE-SPECIFIC APPLICABLE REQUIREMENTS

The permit holder shall comply with all applicable requirements, including those specified in the BAAQMD and SIP Rules and Regulations and other federal requirements cited below. The requirements cited in the following tables apply in a specific manner to the indicated source(s).

The dates in parentheses in the Title column identify the versions of the regulations being cited and are, as applicable:

1. BAAQMD regulation(s): The date(s) of adoption or most recent amendment of the regulation by the District Board of Directors
2. Any federal requirement, including a version of a District regulation that has been approved into the SIP: The most recent date of EPA approval of any portion of the rule, encompassing all actions on the rule through that date

The full text of each permit condition cited is included in Section VI, Permit Conditions, of this permit. The full language of SIP requirements is ~~included in Appendix A of this permit if the SIP requirements are different from the current BAAQMD requirements on EPA Region 9's website. The address is included at the end of this permit.~~ All other text may be found in the regulations themselves.

Table IV - A
Source-specific Applicable Requirements
S1 – KELLER CANYON LANDFILL

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 1	General Provisions and Definitions (10/7/985/2/01)		
1-523	Parametric Monitoring and Recordkeeping Procedures	<u>Y</u>	
1-523.1	Reporting requirement for periods of inoperation > 24 hours	Y	
1-523.2	Limit on duration of inoperation	Y	
1-523.3	Reporting requirement for violations of any applicable limits	<u>Y</u>	
1-523.4	Records of inoperation, tests, calibrations, adjustments, & maintenance	Y	
<u>1-523.5</u>	<u>Maintenance and calibration</u>	<u>N</u>	
<u>SIP Regulation 1</u>	<u>General Provisions and Definitions (6/28/99)</u>		
<u>1-523</u>	<u>Parametric Monitoring and Recordkeeping Procedures</u>	<u>Y</u> ¹	
<u>1-523.3</u>	<u>Reports of Violations</u>	<u>Y</u> ¹	
<u>1-523.5</u>	<u>Maintenance and Calibration</u>	<u>Y</u> ¹	

IV. Source-Specific Applicable Requirements

Table IV - A
Source-specific Applicable Requirements
S1 – KELLER CANYON LANDFILL

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann No. 1 Limitation	Y	
6-305	Visible Particles	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Regulation 8, Rule 2	Organic Compounds – Miscellaneous Operations (6/15/94)		
8-2-301	Miscellaneous Operations	Y	
BAAQMD Regulation 8, Rule 34	Organic Compounds – Solid Waste Disposal Sites (10/6/99)		
8-34-113	Limited Exemption, Inspection and Maintenance	NY	
8-34-113.1	Emission Minimization Requirement	Y	
8-34-113.2	Shutdown Time Limitation	NY	
8-34-113.3	Recordkeeping Requirement	Y	
8-34-116	Limited Exemption, Well Raising	NY	
8-34-116.1	New Fill	NY	
8-34-116.2	Limits on Number of Wells Shutdown	NY	
8-34-116.3	Shutdown Duration Limit	NY	
8-34-116.4	Capping Well Extensions	NY	
8-34-116.5	Well Disconnection Records	NY	
8-34-117	Limited Exemption, Gas Collection System Components	NY	
8-34-117.1	Necessity of Existing Component Repairs/Adjustments	NY	
8-34-117.2	New Components are Described in Collection and Control System Design Plan	NY	
8-34-117.3	Meets Section 8-34-118 Requirements	NY	
8-34-117.4	Limits on Number of Wells Shutdown	NY	
8-34-117.5	Shutdown Duration Limit	NY	
8-34-117.6	Well Disconnection Records	NY	
8-34-118	Limited Exemption, Construction Activities	NY	
8-34-118.1	Construction Plan	NY	
8-34-118.2	Activity is Required to Maintain Compliance with this Rule	NY	
8-34-118.3	Required or Approved by Other Enforcement Agencies	NY	

IV. Source-Specific Applicable Requirements

Table IV - A
Source-specific Applicable Requirements
S1 – KELLER CANYON LANDFILL

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
8-34-118.4	Emission Minimization Requirement	<u>NY</u>	
8-34-118.5	Excavated Refuse Requirements	<u>NY</u>	
8-34-118.6	Covering Requirements for Exposed Refuse	<u>NY</u>	
8-34-118.7	Installation Time Limit	<u>NY</u>	
8-34-118.8	Capping Required for New Components	<u>NY</u>	
8-34-118.9	Construction Activity Records	<u>NY</u>	
8-34-301	Landfill Gas Collection and Emission Control System Requirements	<u>NY</u>	
8-34-301.1	Continuous Operation	<u>NY</u>	
8-34-301.2	Collection and Control Systems Leak Limitations	<u>NY</u>	
8-34-303a	Landfill Surface Requirements	Y	<u>Expires 7/1/02</u>
<u>8-34-303b</u>	<u>Landfill Surface Requirements</u>	<u>N</u>	<u>7/1/02</u>
8-34-304	Gas Collection System Installation Requirements	<u>NY</u>	
8-34-304.1	Based on Waste Age For Inactive or Closed Areas	<u>NY</u>	
8-34-304.2	Based on Waste Age For Active Areas	<u>NY</u>	
8-34-304.3	Based on Amount of Decomposable Waste Accepted	<u>NY</u>	
8-34-304.4	Based on NMOC Emission Rate	<u>NY</u>	
8-34-305	Wellhead Requirements	<u>NY</u>	<u>7/1/02</u>
8-34-305.1	Operate Under Vacuum	<u>NY</u>	<u>7/1/02</u>
8-34-305.2	Temperature < 55 °C	<u>NY</u>	<u>7/1/02</u>
8-34-305.3	Nitrogen < 20% or	<u>NY</u>	<u>7/1/02</u>
8-34-305.4	Oxygen < 5%	<u>NY</u>	<u>7/1/02</u>
8-34-405	Design Capacity Reports	<u>NY</u>	
8-34-408	Collection and Control System Design Plan	<u>NY</u>	
8-34-408.2	Sites With Existing Collection and Control Systems	<u>NY</u>	
8-34-411	Annual Report	<u>NY</u>	
8-34-412	Compliance Demonstration Tests	<u>NY</u>	
8-34-413	Performance Test Report	<u>NY</u>	
8-34-414	Repair Schedule for Wellhead Excesses	<u>NY</u>	<u>7/1/02</u>
8-34-414.1	Records of Excesses	<u>NY</u>	<u>7/1/02</u>
8-34-414.2	Corrective Action	<u>NY</u>	<u>7/1/02</u>
8-34-414.3	Collection System Expansion	<u>NY</u>	<u>7/1/02</u>
8-34-414.4	Operational Due Date for Expansion	<u>NY</u>	<u>7/1/02</u>

IV. Source-Specific Applicable Requirements

Table IV - A
Source-specific Applicable Requirements
S1 – KELLER CANYON LANDFILL

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
8-34-415	Repair Schedule for Surface Leak Excesses	<u>NY</u>	<u>7/1/02</u>
8-34-415.1	Records of Excesses	<u>NY</u>	<u>7/1/02</u>
8-34-415.2	Corrective Action	<u>NY</u>	<u>7/1/02</u>
8-34-415.3	Re-monitor Excess Location Within 10 Days	<u>NY</u>	<u>7/1/02</u>
8-34-415.4	Re-monitor Excess Location Within 1 Month	<u>NY</u>	<u>7/1/02</u>
8-34-415.5	If No More Excesses, No Further Re-Monitoring	<u>NY</u>	<u>7/1/02</u>
8-34-415.6	Additional Corrective Action	<u>NY</u>	<u>7/1/02</u>
8-34-415.7	Re-monitor Second Excess Within 10 days	<u>NY</u>	<u>7/1/02</u>
8-34-415.8	Re-monitor Second Excess Within 1 Month	<u>NY</u>	<u>7/1/02</u>
8-34-415.9	If No More Excesses, No Further Re-monitoring	<u>NY</u>	<u>7/1/02</u>
8-34-415.10	Collection System Expansion for Third Excess in a Quarter	<u>NY</u>	<u>7/1/02</u>
8-34-415.11	Operational Due Date for Expansion	<u>NY</u>	<u>7/1/02</u>
8-34-416	Cover Repairs	<u>NY</u>	
8-34-501	Operating Records	<u>NY</u>	
8-34-501.1	Collection System Downtime	<u>NY</u>	
8-34-501.4	Testing	<u>NY</u>	
8-34-501.6	Leak Discovery and Repair Records	<u>NY</u>	
8-34-501.7	Waste Acceptance Records	<u>NY</u>	
8-34-501.8	Non-decomposable Waste Records	<u>NY</u>	
8-34-501.9	Wellhead Excesses and Repair Records	<u>NY</u>	<u>7/1/02</u>
8-34-501.10	Gas Flow Rate Records for All Emission Control -Systems	<u>NY</u>	
8-34-501.12	Records Retention for 5 Years	<u>NY</u>	
8-34-503	Landfill Gas Collection and Emission Control System Leak Testing	<u>Y</u>	
8-34-504	Portable Hydrocarbon Detector	Y	
8-34-505	Well Head Monitoring	<u>NY</u>	<u>7/1/02</u>
8-34-506	Landfill Surface Monitoring	<u>NY</u>	<u>7/1/02</u>
8-34-508	Gas Flow Meter	<u>NY</u>	
8-34-510	Cover Integrity Monitoring	<u>NY</u>	
SIP			
Regulation 8, Rule 34	Organic Compounds—Solid Waste Disposal Sites (6/15/94)		
<u>8-34-113</u>	<u>Exemption, Inspection and Maintenance</u>	<u>Y</u>	
<u>8-34-113.1</u>	<u>Emission Minimization Requirement</u>	<u>Y</u>	

IV. Source-Specific Applicable Requirements

Table IV - A
Source-specific Applicable Requirements
S1 – KELLER CANYON LANDFILL

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
8-34-113.2	Shutdown Time Limitation	Y⁺	
8-34-113.3	Recordkeeping Requirement	Y	
8-34-301	Landfill Gas Collection and Emission Control System Requirements	Y	
8-34-301.1	Collection and Control Systems Leak Limitations	Y	
8-34-301.4	Continuous Operation	Y	
8-34-303	Landfill Surface Requirement	Y⁺	
8-34-501	Operating Records	Y	
8-34-501.1	Collection System Downtime	Y	
8-34-501.4	Records of Testing for Compliance with 8-34-111.3 or 301	Y	
8-34-501.6	Records Retention	Y	
8-34-503	Landfill Gas Collection System Testing	Y	
8-34-504	Portable Hydrocarbon Detector	Y	
BAAQMD Regulation 8, Rule 40	Organic Compounds – Aeration of Contaminated Soil and Removal of Underground Storage Tanks (12/15/99)		
8-40-110	Exemption, Storage Pile	Y	
8-40-112	Exemption, Sampling	Y	
8-40-113	Exemption, Non-Volatile Hydrocarbons	Y	
8-40-116	Exemption, Small Volume	NY	
8-40-116.1	Volume does not exceed 1 cubic yard	NY	
8-40-116.2	Volume does not exceed 8 cubic yards, organic content does not exceed 500 ppmw, may be used only once per quarter	NY	
8-40-117	Exemption, Accidental Spills	NY	
8-40-118	Exemption, Aeration Projects of Limited Impact	NY	
8-40-301	Uncontrolled Contaminated Soil Aeration	NY	
8-40-304	Active Storage Piles	NY	
8-40-305	Inactive Storage Piles	NY	
SIP Regulation 8, Rule 40	Organic Compounds – Aeration of Contaminated Soil and Removal of Underground Storage Tanks (6/15/94)		
8-40-110	Exemption, Storage Pile	Y	

⁺ This section has been removed from BAAQMD Regulations because it has been superseded. Nevertheless, the source must comply with this regulation until US EPA has reviewed and approved (or disapproved) the District's revision of the regulation.

IV. Source-Specific Applicable Requirements

Table IV - A
Source-specific Applicable Requirements
S1 – KELLER CANYON LANDFILL

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
8-40-112	Exemption, Sampling	Y	
8-40-113	Exemption, Non-Volatile Hydrocarbons	Y	
8-40-301	Uncontrolled Aeration	Y⁺	
8-40-302	Controlled Aeration	Y⁺	
8-40-303	Storage Piles	Y⁺	
8-40-403	Reporting, Aeration of Contaminated Soil	Y	
8-40-403.1	Total Quantity of Soil to be Aerated	Y	
8-40-403.2	Quantity of Soil to be Aerated per Day	Y	
8-40-403.3	Average Degree of Contamination or Total Organic Content in Soil	Y	
8-40-403.4	Chemical Composition of Contaminating Organics	Y	
8-40-403.5	Basis for Above Estimations	Y	
BAAQMD Regulation 9, Rule 2	Inorganic Gaseous Pollutants – Hydrogen Sulfide (10/6/99)		
9-2-301	Limitations on Hydrogen Sulfide	N	
BAAQMD Regulation 11, Rule 1	Hazardous Pollutants – Lead (3/17/82)		
11-1-302	Ground Level Concentration Limit Without Background	Y	
BAAQMD Regulation 11, Rule 3	Hazardous Pollutants – Beryllium (3/17/82)		
11-3-301	Emission Limitation	N	
11-3-303	Ambient Concentration Limits	N	
BAAQMD Regulation 11, Rule 14	Hazardous Pollutants – Asbestos-Containing Serpentine (7/17/91)		
11-14-301	Prohibition of Use for Surfacing Operations	N	
11-14-501	Maintenance of Records	N	
40 CFR Part 60, Subpart A	Standards of Performance for New Stationary Sources – General Provisions (5/4/98)		
60.4(b)	Requires Submission of Requests, Reports, Applications, and Other Correspondence to the Administrator	Y	

IV. Source-Specific Applicable Requirements

Table IV - A
Source-specific Applicable Requirements
S1 – KELLER CANYON LANDFILL

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
60.7	Notification and Record Keeping	Y	
60.8	Performance Tests	Y	
60.11	Compliance with Standards and Maintenance Requirements	Y	
60.11(a)	Compliance determined by performance tests	Y	
60.11(d)	Control devices operated using good air pollution control practice	Y	
60.12	Circumvention	Y	
60.13	Monitoring Requirements	Y	
60.13(a)	Applies to all continuous monitoring systems	Y	
60.13(b)	Monitors shall be installed and operational before performing performance tests	Y	
60.13(e)	Continuous monitors shall operate continuously	Y	
60.13(f)	Monitors shall be installed in proper locations	Y	
60.13(g)	Multiple monitors are required for multiple stacks	Y	
60.14	Modification	Y	
60.15	Reconstruction	Y	
60.19	General Notification and Reporting Requirements	Y	
40 CFR Part 60, Subpart WWW	Standards of Performance for New Stationary Sources – Standards of Performance for Municipal Solid Waste Landfills (2/24/99)		
60.752	Standards for Air Emissions from Municipal Solid Waste Landfills	Y	
60.752(b)	Requirements for MSW Landfills with Design Capacity equal to or greater than 2.5 million Mg and 2.5 million m ³ (Large Designated Facilities)	Y	
60.752(b)(2)	Comply with all requirements in sections (b)(2)(i through iv)	Y	
60.752 (b)(2)(i)	Submit a Collection and Control System Design Plan	Y	
60.752 (b)(2)(i)(A)	The collection and control system in the Design Plan shall comply with 60.752(b)(2)(ii)	Y	
60.752 (b)(2)(i)(B)	Design Plan shall include all proposed alternatives to 60.753 through 60.758	Y	
60.752 (b)(2)(i)(C)	Design Plan shall conform to 60.759 (active collection system) or demonstrate sufficiency of proposed alternatives	Y	

IV. Source-Specific Applicable Requirements

Table IV - A
Source-specific Applicable Requirements
S1 – KELLER CANYON LANDFILL

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
60.752 (b)(2)(ii)	Install a collection and control system	Y	
60.752 (b)(2)(iii)	Route collected gases to a control system.	Y	
60.752 (b)(2)(iv)	Operate in accordance with 60.753, 60.755, and 60.756	Y	
60.752(c)	Title V Operating Permit Requirements	Y	
60.752(c)(1)	Subject date is June 10, 1996 for Landfills new or modified between May 30, 1991 and March 12, 1996	Y	
60.753	Operational Standards for Collection and Control Systems	Y	
60.753(a)	Operate a Collection System in each area or cell in which:	Y	
60.753(a)(1)	Active Cell – solid waste in place for 5 years or more	Y	
60.753(a)(2)	Closed/Final Grade – solid waste in place for 2 years or more	Y	
60.753(b)	Operate each wellhead under negative pressure unless:	Y	
60.753(b)(1)	Fire or increased well temperature or to prevent fire	Y	
60.753(b)(2)	Use of geomembrane or synthetic cover (subject to alternative pressure limits)	Y	
60.753(b)(3)	Decommissioned well after approval received for shut-down	Y	
60.753(c)	Operate each wellhead at < 55 °C, and either < 20% N ₂ or < than 5% O ₂ (or other approved alternative levels)	Y	
60.753(c)(1)	N ₂ determined by Method 3C	Y	
60.753(c)(2)	O ₂ determined by 3A and as described in (2)(i-v)	Y	
60.753(d)	Surface Leak Limit is less than 500 ppm methane above background at landfill surface. This section also describes some surface monitoring procedures.	Y	
60.753(e)	Vent all collected gases to a control system complying with 60.752(b)(2)(iii). If collection or control system inoperable, shut down gas mover and close all vents within 1 hour	Y	
60.753(g)	If monitoring demonstrates that 60.753(b), (c), or (d) are not being met, corrective action must be taken	Y	
60.754	Test Methods and Procedures	Y	
60.754(a)	NMOC Calculation Procedures for NMOC Emission Rate Reports and Comparison to 50 Mg/Year Standard	Y	

IV. Source-Specific Applicable Requirements

Table IV - A
Source-specific Applicable Requirements
S1 – KELLER CANYON LANDFILL

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
60.754(a)(1)	Calculate NMOC Emission Rate using either or both of the equations in 60.754(a)(1)(i-ii) with the listed default values	Y	
60.754(a)(1)(i)	Equation for known year-to-year waste acceptance rate	Y	
60.754(a)(1)(ii)	Equation for unknown year-to-year waste acceptance rate	Y	
60.754(a)(2)	Tier 1 - compare calculated NMOC emission rate to 50 Mg/year	Y	
60.754(a)(2)(ii)	If NMOC Emission Rate > 50 Mg/year, comply with 60.752(b)(2) or determine a site-specific NMOC concentration and follow 60.754(a)(3).	Y	
60.754(c)	For PSD, NMOC emissions shall be calculated using AP-42	Y	
60.754(d)	Test Methods for Performance Test (Method 18 or 25C)	Y	
60.755	Compliance Provisions	Y	
60.755(a)	For Gas Collection Systems	Y	
60.755(a)(1)	Calculation procedures for maximum expected gas generation flow rate	Y	
60.755(a)(1)(i)	Equation for unknown year-to-year waste acceptance rate	Y	
60.755(a)(1)(ii)	Equation for known year-to-year waste acceptance rate	Y	
60.755(a)(2)	Vertical wells and horizontal collectors shall be of sufficient density to meet all performance specifications	Y	
60.755(a)(3)	Measure wellhead pressure monthly. If pressure is positive, take corrective action (final corrective action = expand system within 120 days of initial positive pressure reading)	Y	
60.755(a)(4)	Expansion not required during first 180 days after startup.	Y	
60.755(a)(5)	Monitor wellheads monthly for temperature and either nitrogen or oxygen. If readings exceed limits, take corrective action up to expanding system within 120 days of first excess.	Y	
60.755(b)	Wells shall be placed in cells as described in Design Plan and no later than 60 days after:	Y	
60.755(b)(1)	Five years after initial waste placement in cell, for active cells	Y	
60.755(b)(2)	Two years after initial waste placement in cell, for closed/final grade cells.	Y	

IV. Source-Specific Applicable Requirements

Table IV - A
Source-specific Applicable Requirements
S1 – KELLER CANYON LANDFILL

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
60.755(c)	Procedures for complying with surface methane standard	Y	
60.755(c)(1)	Quarterly monitoring of surface and perimeter	Y	
60.755(c)(2)	Procedure for determining background concentration	Y	
60.755(c)(3)	Method 21 except probe inlet placed 5-10 cm above ground	Y	
60.755(c)(4)	Excess is any reading of 500 ppmv or more. Take corrective action indicated below (i-v).	Y	
60.755(c)(4)(i)	Mark and record location of excess	Y	
60.755(c)(4)(ii)	Repair cover or adjust vacuum. Re-monitor within 10 calendar days.	Y	
60.755(c)(4)(iii)	If still exceeding 500 ppmv, take additional corrective action. Re-monitor within 10 calendar days of 2 nd excess.	Y	
60.755(c)(4)(iv)	Re-monitor within 1 month of initial excess.	Y	
60.755(c)(4)(v)	For any location with 3 monitored excesses in a quarter, additional collectors (or other approved collection system repairs) shall be operational within 120 days of 1 st excess.	Y	
60.755(c)(5)	Monitor cover integrity monthly and repair as needed.	Y	
60.755(d)	Instrumentation and procedures for complying with 60.755(c).	Y	
60.755(d)(1)	Portable analyzer meeting Method 21	Y	
60.755(d)(2)	Calibrated with methane diluted to 500 ppmv in air	Y	
60.755(d)(3)	Use Method 21, Section 4.4 instrument evaluation procedures	Y	
60.755(d)(4)	Calibrate per Method 21, Section 4.2 immediately before monitoring.	Y	
60.755(e)	Provisions apply at all times except during startup, shutdown, or malfunction, provided the duration of these shall not exceed 5 days for collection systems or 1 hour for control systems.	Y	
60.756	Monitoring of Operations	Y	
60.756(a)	For active collection systems, install wellhead sampling port	Y	
60.756(a)(1)	Measure gauge pressure in wellhead on a monthly basis	Y	
60.756(a)(2)	Measure nitrogen or oxygen concentration in wellhead gas on a monthly basis.	Y	
60.756(a)(3)	Measure temperature of wellhead gas on a monthly basis.	Y	

IV. Source-Specific Applicable Requirements

Table IV - A
Source-specific Applicable Requirements
S1 – KELLER CANYON LANDFILL

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
60.756(b)(2)	Device that records flow to or bypass of the control device (i or ii below)	Y	
60.756(b)(2)(i)	Install, calibrate, and maintain a device that records flow to the control device at least every 15 minutes.	Y	
60.756(e)	Procedures for requesting alternative monitoring parameters	Y	
60.756(f)	Monitor surface on a quarterly basis.	Y	
60.757	Reporting Requirements	Y	
60.757(a)	Submit an Initial Design Capacity Report	Y	
60.757(a)(3)	Amended Design Capacity Report required within 90 days of receiving a permitted increase in design capacity or within 90 days of an annual density calculation that results in a design capacity over the thresholds.	Y	
60.757(b)	Submit Initial and Annual NMOC Emission Rate Report	Y	
60.757(b)(3)	Sites with collection and control systems operating in compliance with this subpart are exempt from (b)(1) and (b)(2) above.	Y	
60.757(c)	Submit a Collection and Control System Design Plan within 1 year of first NMOC emission rate report showing NMOC > 50 MG/year, except as follows	Y	
60.757(f)	Submit Annual Reports containing information required by (f)(1) through (f)(6)	Y	
60.757(f)(1)	Value and length of time for exceedance of parameters monitored per 60.756(a), (b) or (d)	Y	
60.757(f)(2)	Description and duration of all periods when gas is diverted from the control device by a by-pass line	Y	
60.757(f)(3)	Description and duration of all periods when control device was not operating for more than 1 hour	Y	
60.757(f)(4)	All periods when collection system was not operating for more than 5 days.	Y	
60.757(f)(5)	Location of each surface emission excess and all re-monitoring dates and concentrations.	Y	
60.757(f)(6)	Location and installation dates for any wells or collectors added as a result of corrective action for a monitored excess.	Y	
60.757(g)	Initial Performance Test Report Requirements (g)(1-6)	Y	

IV. Source-Specific Applicable Requirements

Table IV - A
Source-specific Applicable Requirements
S1 – KELLER CANYON LANDFILL

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
60.757(g)(1)	Diagram of collection system showing positions of all existing collectors, proposed positions for future collectors, and areas to be excluded from control.	Y	
60.757(g)(2)	Basis for collector positioning to meet sufficient density req.	Y	
60.757(g)(3)	Documentation supporting percentage of asbestos or non-degradable material claims for areas without a collection system.	Y	
60.757(g)(4)	For areas excluded from collection due to non-productivity, calculations and gas generation rates for each non-productive area and the sum for all nonproductive areas.	Y	
60.757(g)(5)	Provisions for increasing gas mover equipment if current system is inadequate to handle maximum projected gas flow rate.	Y	
60.757(g)(6)	Provisions for control of off-site migration	Y	
60.758	Recordkeeping Requirements	Y	
60.758(a)	Design Capacity and Waste Acceptance Records (retain 5 years)	Y	
60.758(b)	Collection and Control Equipment Records (retain for life of control equipment except 5 years for monitoring data)	Y	
60.758(b)(1)	Collection System Records	Y	
60.758(b)(1)(i)	Maximum expected gas generation flow rate.	Y	
60.758(b)(1)(ii)	Density of wells and collectors	Y	
60.758(c)	Records of parameters monitored pursuant to 60.756 and periods of operation when boundaries are exceeded (retain for 5 years).	Y	
60.758(c)(2)	Records of continuous flow to control device or monthly inspection records if seal and lock for bypass valves	Y	
60.758(d)	Plot map showing location of all existing and planned collectors with a unique label for each collector (retain for life of collection system)	Y	
60.758(d)(1)	Installation date and location of all newly installed collectors	Y	
60.758(d)(2)	Records of nature, deposition date, amount, and location of asbestos or non-degradable waste excluded from control	Y	
60.758(e)	Records of any exceedance of 60.753, location of exceedance and re-monitoring dates and data (for wellheads and surface). Retain for 5 years.	Y	
60.759	Specifications for Active Collection Systems	Y	

IV. Source-Specific Applicable Requirements

Table IV - A
Source-specific Applicable Requirements
S1 – KELLER CANYON LANDFILL

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
60.759(a)	Active wells and collectors shall be at sufficient density	Y	
60.759(a)(1)	Collection System in refuse shall be certified by PE to achieve comprehensive control of surface gas emissions	Y	
60.759(a)(2)	Collection Systems (active or passive) outside of refuse shall address migration control	Y	
60.759(a)(3)	All gas producing areas shall be controlled except as described below (i-iii).	Y	
60.759(a)(3)(i)	Any segregated area of asbestos or non-degradable material only may be excluded, if documented adequately per 60.758(d).	Y	
60.759(a)(3)(ii)	Any non-productive areas may be excluded from control, provided total NMOC emissions from all excluded areas is < 1% of total NMOC emissions from landfill. Document amount, location, and age of waste and all calculations for each excluded area.	Y	
60.759(a)(3)(iii)	For calculating NMOC emissions, values for k and concentration of NMOC that have been previously approved shall be used or defaults if no values were approved. All non-degradable wastes that are being subtracted from total wastes for NMOC calculations must be documented adequately.	Y	
60.759(b)	Gas Collection System Components	Y	
60.759(b)(1)	Must be constructed of PVC, HDPE, fiberglass, stainless steel, or other approved material and of suitable dimensions to convey projected gas amounts and withstand settling, traffic, etc.	Y	
60.759(b)(2)	Collectors shall not endanger liner, shall manage condensate and leachate, and shall prevent air intrusion and surface leaks.	Y	
60.759(b)(3)	Header connection assemblies shall include positive closing throttle valve, seals and couplings to prevent leaks, at least one sampling port, and shall be constructed of PVC, HDPE, fiberglass, stainless steel, or other approved materials.	Y	
60.759(c)	Gas Mover Equipment shall be sized to handle maximum expected gas generation rate over the intended period of use.	Y	
60.759(c)(1)	For existing systems, flow data shall be used to project maximum flow rate.	Y	

IV. Source-Specific Applicable Requirements

Table IV - A
Source-specific Applicable Requirements
S1 – KELLER CANYON LANDFILL

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
60.759(c)(2)	For new systems, gas generation rate shall be calculated per 60.755(a)(1)	Y	
BAAQMD Condition #17309			
Part 1	Operating Time Restrictions (Cumulative Increase)	Y	
Part 2	Waste Acceptance Rate Limit (Cumulative Increase and Regulation 2-1-301)	Y	
Part 3, subparts a-d	Daily Cover Requirements and Limitations (Regulation 1-301 and Cumulative Increase)	Y	
Part 4	Road Surfacing Requirements for Parking and Maintenance Areas (Cumulative Increase)	Y	
Part 5, subparts a-d	Road Surfacing Requirements for On-Site Road Ways (Cumulative Increase)	Y	
Part 6	Speed Limits for Unpaved Roads (Cumulative Increase)	Y	
Part 7	Road Surfacing Requirements for Unpaved Roads (Cumulative Increase)	Y	
Part 8, subparts a-d	Minimum Water and Dust Suppressant Application Rates for Unpaved Roads (Cumulative Increase)	Y	
Part 9	Water Truck Requirements (Cumulative Increase)	Y	
Part 10	Watering Requirements for Paved and Aggregate Based Road Ways (Cumulative Increase)	Y	
Part 11, subparts a-d	Traffic Volume Limitations (Cumulative Increase)	Y	
Part 12, subparts a-c	Trip Length Limitations for Heavy Duty Vehicles (Cumulative Increase)	Y	
Part 13	Watering Requirements for Active Face, Cover Soil Areas, and Off-Road Soil Areas (Cumulative Increase)	Y	
Part 14	Vegetation Requirements for Inactive Cover Soil Stockpiles (CEQA, Dust Mitigation Measures)	N	
Part 15	Vegetation Requirements for Completed Landfill Phases (CEQA, Dust Mitigation Measures)	N	
Part 16, subparts a-l	Record Keeping Requirements (Cumulative Increase and Regulation 2-6-501)	Y	

IV. Source-Specific Applicable Requirements

Table IV - A
Source-specific Applicable Requirements
S1 – KELLER CANYON LANDFILL

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
Part 17	Control Requirements for Collected Landfill Gas (Regulations 8-34-301 and 8-34-303 and 40 CFR 60.752(b)(2)(iii), 60.753(e) and 60.755(e))	Y	
Part 18	Continuous Operating Requirement for Landfill Gas Collection System (Regulation 8-34-301 and 40 CFR 60.753(b and c) and 60.755(e))	Y	
Part 19	Annual Report on Waste Placement in Uncontrolled Areas (Regulations 8-34-301, 8-34-303, and 8-34-304)	Y	
Part 20, subparts a-b	Well Installation and Design Parameters (Regulations 8-34-303, 8-34-304, and 8-34-305 and 40 CFR 60.755(a) and 60.759)	Y	
Part 31	Annual Landfill Gas Characterization Test (Toxic Risk Management Policy, Regulation 8-34-301, and NSPS)	Y	
Part 32	Limits on Toxic Air Contaminants in Landfill Gas (Toxic Risk Management Policy)	N	
Part 33, subparts a-h	Precursor Organic Compound Emission Limit and Calculation Procedures (Offsets)	Y	
Part 34	Landfill Gas Sulfur Content Limit and Testing Procedures (Regulations 9-1-302 and 2-6-503)	Y	
Part 36, subparts a-c	Contaminated Soil Throughput Limit and Records (Regulation 8-2-301)	Y	
Part 37, subparts a-m	Handling Procedures for Soil Containing Volatile Organic Compounds (Regulations 2-1-403 , 8-40-301, 8-40-304, and 8-40-305)	NY	
Part 38	Conditions under which non-federally enforceable portions of Regulation 8, Rules 34 and 40 will become federally enforceable (2-6-207)	Y	

- 1 This section has been removed from BAAQMD Regulations because it has been superseded. Nevertheless, the source must comply with this regulation until US EPA has reviewed and approved (or disapproved) the District's revision of the regulation.

IV. Source-Specific Applicable Requirements

Table IV – B
Source-specific Applicable Requirements
S2 – WIPE CLEANING OPERATION

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 8, Rule 16	Organic Compounds – Solvent Cleaning Operations (9/16/9810/16/02)		
8-16-501	Solvent Records		
8-16-501.2	Facility-wide, annual records of makeup solvent use	N	
8-16-501.5	Record retention	N	
SIP Regulation 8, Rule 16	Organic Compounds – Solvent Cleaning Operations (6/15/94)		
8-16-501	Solvent Records		
8-16-501.2	Facility-wide, quarterly records of makeup solvent use	Y ¹	
BAAQMD Condition #9527			
Part 1	Solvent Usage Limits (Cumulative Increase and Regulation 2-1-301)	Y	
Part 2, subparts a-b	Record Keeping Requirements (Cumulative Increase and Regulations 8-16-501 and 2-6-501)	Y	

¹ This section has been removed from BAAQMD Regulations because it has been superseded. Nevertheless, the source must comply with this regulation until US EPA has reviewed and approved (or disapproved) the District's revision of the regulation.

IV. Source-Specific Applicable Requirements

Table IV – C
Source-specific Applicable Requirements
S3 – YARD AND GREEN WASTE STOCKPILES

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann No. 1 Limitation	Y	
6-305	Visible Particles	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Condition #16462			
Part 1	Limit on Yard and Green Waste Received (Cumulative Increase)	Y	
Part 2	Watering Requirements (Regulation 6-301 6-305 , and Regulation 2-6-503)	Y	
Part 3	Maximum Storage Time for Incoming Waste Prior to Processing (Regulation 1-301)	N	
Part 4	Maximum Storage Time for “Odorous” Stockpile (Regulation 1-301)	N	
Part 5	Public Nuisance Control Measures (Regulation 1-301)	N	
Part 6, subparts a-d	Record Keeping Requirements (Cumulative Increase and Regulations 1-301 , 2-6-501 , 6-301 and 6-3052-6-501)	Y	

IV. Source-Specific Applicable Requirements

Table IV – D
Source-specific Applicable Requirements
A1 – LANDFILL GAS FLARE

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 1	General Provisions and Definitions (5/2/0140/7/98)		
1-523	Parametric Monitoring and Recordkeeping Procedures	Y N	
1-523.1	Reporting requirement for periods of inoperation > 24 hours	Y	
1-523.2	Limit on duration of inoperation	Y	
1-523.3	Reporting requirement for violations of any applicable limits	Y N	
1-523.4	Records of inoperation, tests, calibrations, adjustments, & maintenance	Y	
1-523.5	Maintenance and calibration	N	
SIP Regulation 1	General Provisions and Definitions (6/28/1999)		
1-523	Parametric Monitoring and Recordkeeping Procedures	Y ¹	
1-523.3	Reports of Violations	Y ¹	
1-523.5	Maintenance and Calibration	Y ¹	
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann No. 1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Regulation 8, Rule 34	Organic Compounds - Solid Waste Disposal Sites (10/6/99)		
8-34-113	Limited Exemption, Inspection and Maintenance	N Y	
8-34-113.1	Emission Minimization Requirement	Y	
8-34-113.2	Shutdown Time Limitation	N Y	
8-34-113.3	Recordkeeping Requirement	Y	
8-34-301	Landfill Gas Collection and Emission Control System Requirements	N Y	
8-34-301.1	Continuous Operation	N Y	
8-34-301.2	Collection and Control Systems Leak Limitations	N Y	
8-34-301.3a	Enclosed Flare Destruction Efficiency	N	Expires 7/1/02
8-34-301.3b	Limits for Enclosed Flares	N Y	7/1/02
8-34-408	Collection and Control System Design Plans	N Y	
8-34-408.2	Sites With Existing Collection and Control Systems	N Y	
8-34-411	Annual Report	N Y	

IV. Source-Specific Applicable Requirements

Table IV – D
Source-specific Applicable Requirements
A1 – LANDFILL GAS FLARE

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
8-34-412	Compliance Demonstration Tests	<u>NY</u>	
8-34-413	Performance Test Report	<u>NY</u>	
8-34-501	Operating Records	<u>NY</u>	
8-34-501.2	Emission Control System Downtime	<u>NY</u>	
8-34-501.3	Continuous Temperature Records for Enclosed Combustors	<u>NY</u>	
8-34-501.4	Testing	<u>NY</u>	
8-34-501.6	Leak Discovery and Repair Records	<u>NY</u>	
8-34-501.10	Gas Flow Rate Records for All Emission Control Systems	<u>NY</u>	
8-34-501.12	Records Retention for 5 Years	<u>NY</u>	
8-34-503	Landfill Gas Collection and Emission Control System Leak Testing	Y	
8-34-504	Portable Hydrocarbon Detector	Y	
8-34-507	Continuous Temperature Monitor and Recorded	<u>NY</u>	
8-34-508	Gas Flow Meter	<u>NY</u>	
SIP Regulation 8, Rule 34	Organic Compounds – Solid Waste Disposal Sites (6/15/94)		
8-34-113	Exemption, Inspection and Maintenance	Y	
8-34-113.1	Emission Minimization Requirement	Y	
8-34-113.2	Shutdown Time Limitation	Y⁺	
8-34-113.3	Recordkeeping Requirement	Y	
8-34-301	Landfill Gas Collection and Emission Control System Requirements	Y	
8-34-301.1	Collection and Control Systems Leak Limitations	Y	
8-34-301.2	Enclosed Flare Destruction Efficiency	Y⁺	
8-34-301.4	Continuous Operation	Y	
8-34-501	Operating Records	Y	
8-34-501.2	Emission Control System Downtime	Y	
8-34-501.3	Temperature Monitoring	Y	
8-34-501.4	Records of Testing for Compliance with 8-34-111.3 or 301	Y	
8-34-501.6	Records Retention	Y	
8-34-503	Landfill Gas Collection System Testing	Y	
8-34-504	Portable Hydrocarbon Detector	Y	
BAAQMD Regulation 9, Rule 1	Inorganic Gaseous Pollutants – Sulfur Dioxide (3/15/95)		
9-1-301	Limitations on Ground Level Concentrations	Y	
9-1-302	General Emission Limitations	Y	

IV. Source-Specific Applicable Requirements

Table IV – D
Source-specific Applicable Requirements
A1 – LANDFILL GAS FLARE

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 9, Rule 2	Inorganic Gaseous Pollutants – Hydrogen Sulfide (10/6/99)		
9-2-301	Limitations on Hydrogen Sulfide	N	
40 CFR Part 60, Subpart A	Standards of Performance for New Stationary Sources – General Provisions (5/4/98)		
60.4(b)	Requires Submission of Requests, Reports, Applications, and Other Correspondence to the Administrator	Y	
60.7	Notification and Record Keeping	Y	
60.8	Performance Tests	Y	
60.11	Compliance with Standards and Maintenance Requirements	Y	
60.11(a)	Compliance determined by performance tests	Y	
60.11(d)	Control devices operated using good air pollution control practice	Y	
60.12	Circumvention	Y	
60.13	Monitoring Requirements	Y	
60.13(a)	Applies to all continuous monitoring systems	Y	
60.13(b)	Monitors shall be installed and operational before performing performance tests	Y	
60.13(e)	Continuous monitors shall operate continuously	Y	
60.13(f)	Monitors shall be installed in proper locations	Y	
60.13(g)	Requires multiple monitors for multiple stacks	Y	
60.14	Modification	Y	
60.15	Reconstruction	Y	
60.19	General Notification and Reporting Requirements	Y	
40 CFR Part 60, Subpart WWW	Standards of Performance for New Stationary Sources – Standards of Performance for Municipal Solid Waste Landfills (2/24/99)		
60.752	Standards for Air Emissions from Municipal Solid Waste Landfills	Y	
60.752(b)	Requirements for MSW Landfills with Design Capacity equal to or greater than 2.5 million Mg and 2.5 million m ³ (Large Designated Facilities)	Y	
60.752(b)(2)	Comply with all requirements in sections (b)(2)(i through iv)	Y	
60.752(b)(2)(i)	Submit a Collection and Control System Design Plan	Y	

IV. Source-Specific Applicable Requirements

Table IV – D
Source-specific Applicable Requirements
A1 – LANDFILL GAS FLARE

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
60.752(b)(2)(i)(A)	The collection and control system in the Design Plan shall comply with 60.752(b)(2)(ii)	Y	
60.752(b)(2)(i)(B)	Design Plan shall include all proposed alternatives to 60.753 through 60.758	Y	
60.752(b)(2)(ii)	Install a collection and control system	Y	
60.752(b)(2)(iii)	Route collected gases to a control system meeting the following requirements	Y	
60.752(b)(2)(iii)(B)	Reduce NMOC emissions by 98% by weight or reduce NMOC outlet concentration to less than 20 ppmv as hexane at 3% O ₂ , dry basis, as demonstrated by initial performance test within 180 days of start-up.	Y	
60.752(b)(2)(iv)	Operate in accordance with 60.753, 60.755, and 60.756	Y	
60.753	Operational Standards for Collection and Control Systems	Y	
60.753(e)	Vent all collected gases to a control system complying with 60.752(b)(2)(iii). If collection or control system inoperable, shut down gas mover and close all vents within 1 hour	Y	
60.753(f)	Operate the control system at all times when collected gas is routed to the control system	Y	
60.754	Test Methods and Procedures	Y	
60.754(d)	Test Methods for Performance Test (Method 18 or 25C)	Y	
60.755	Compliance Provisions	Y	
60.755(e)	Provisions apply at all times except during startup, shutdown, or malfunction, provided the duration of these shall not exceed 5 days for collection systems or 1 hour for control systems.	Y	
60.756	Monitoring of Operations	Y	
60.756(b)	Enclosed combustors shall comply with (b)(1) and (b)(2)	Y	
60.756(b)(1)	Temperature monitor and continuous recorder (not required for boilers and process heaters with capacity > 44 MW)	Y	
60.756(b)(2)	Device that records flow to or bypass of the control device (i or ii below)	Y	
60.756(b)(2)(i)	Install, calibrate, and maintain a device that records flow to the control device at least every 15 minutes.	Y	
60.756(e)	Procedures for requesting alternative monitoring parameters	Y	
60.757	Reporting Requirements	Y	

IV. Source-Specific Applicable Requirements

Table IV – D
Source-specific Applicable Requirements
A1 – LANDFILL GAS FLARE

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
60.757(f)	Submit Annual Reports containing information required by (f)(1) through (f)(6)	Y	
60.757(f)(1)	Value and length of time for exceedance of parameters monitored per 60.756(a), (b) or (d)	Y	
60.757(f)(2)	Description and duration of all periods when gas is diverted from the control device by a by-pass line	Y	
60.757(f)(3)	Description and duration of all periods when control device was not operating for more than 1 hour	Y	
60.757(g)	-Initial Performance Test Report Requirements (g)(1-6)	Y	
60.758	Recordkeeping Requirements	Y	
60.758(b)	Collection and Control Equipment Records (retain for life of control equipment except 5 years for monitoring data)	Y	
60.758(b)(2)	Control System Records - enclosed combustors other than boilers or process heaters with heat input > 44 MW	Y	
60.758 (b)(2)(i)	Combustion temperature measured every 15 minutes and averaged over the same time period as the performance test	Y	
60.758 (b)(2)(ii)	Percent NMOC reduction achieved by the control device	Y	
60.758(c)	Records of parameters monitored pursuant to 60.756 and periods of operation when boundaries are exceeded (retain for 5 years).	Y	
60.758(c)(1)	Exceedances subject to record keeping are	Y	
60.758 (c)(1)(i)	All 3-hour periods when average combustion temperature was more than 28 C below the average combustion temperature during the most recent complying performance test	Y	
60.758(c)(2)	Records of continuous flow to control device or monthly inspection records if of seal and lock for bypass valves	Y	
60.758(e)	Records of any exceedance of 60.753(e) or (f)	Y	
BAAQMD Condition #17309			
Part 21	Continuous Operation Requirement (Regulation 8-34-301 and 40 CFR 60.752(b)(2)(iii), 60.753(e), and 60.755(e))	Y	
Part 22	Temperature Monitoring and Recording Requirements (Regulations 2-6-501 and 8-34-501 and 40 CFR 60.756(b))	Y	
Part 23	Minimum Temperature Requirement (RACT, Toxic Risk Management Policy, Regulation 8-34-301, and 40 CFR 60.758(c)(1)(i))	Y	
Part 24	Nitrogen Oxide Emission Limit (RACT and Cumulative Increase)	Y	

IV. Source-Specific Applicable Requirements

Table IV – D
Source-specific Applicable Requirements
A1 – LANDFILL GAS FLARE

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
Part 25	Carbon Monoxide Emission Limit (RACT)	Y	
Part 26	Precursor Organic Compound Emission Limit for Flare (Cumulative Increase)	Y	
Part 27	Gas Flow Meter Requirement (Cumulative Increase and 40 CFR 60.756(b))	Y	
Part 28	Alarm and Automated Control Requirements (Regulation 8-34-301)	Y	
Part 29, subparts a-c	Total Hydrocarbon and Total Non-Methane Organic Compound Destruction Efficiency Requirements (Regulation 8-34-301.3, SIP 8-34-301.2 and 40 CFR 60.752(b)(2)(iii)(B))	Y	
Part 30	Annual Source Testing Requirement (RACT, Regulation 8-34-301, and 40 CFR 60.752(b)(2)(iii))	Y	
Part 31	Annual Landfill Gas Characterization Test (Toxic Risk Management Policy, Regulation 8-34-301, and NSPS)	Y	
Part 32	Limits on Toxic Air Contaminants in Landfill Gas (Toxic Risk Management Policy)	N	
Part 33, subparts a-h	Precursor Organic Compound Emission Limit and Calculation Procedures (Offsets)	Y	
Part 34	Landfill Gas Sulfur Content Limit and Testing Procedures (Regulations 9-1-302 and 2-6-503)	Y	
Part 35	Heat Input Limits for A-1 Flare (Regulation 2-1-301)	Y	
Part 38	Conditions under which non-federally enforceable portions of Regulation 8, Rules 34 and 40 will become federally enforceable (2-6-207)	Y	

- 1 This section has been removed from BAAQMD Regulations because it has been superseded. Nevertheless, the source must comply with this regulation until US EPA has reviewed and approved (or disapproved) the District's revision of the regulation.

V. SCHEDULE OF COMPLIANCE

The permit holder shall comply with all applicable requirements cited in this permit. The permit holder shall also comply with applicable requirements that become effective during the term of this permit on a timely basis.

VI. PERMIT CONDITIONS

Any condition that is preceded by an asterisk is not federally enforceable.

Condition # 9527

For S - 2, WIPE CLEANING OPERATION:

~~Conditions for S-2~~

1. The net solvent usage at this source shall not exceed 100 gallons during any consecutive 12-month period nor 0.75 gallons during any day. [Basis: Cumulative Increase and Regulation 2-1-301]
2. In order to ensure compliance with this condition, the following records shall be maintained on site and made available for District inspection for 5 years from the date a record is made:
 - a. The type, VOC content and amount of solvent used monthly.
 - b. The monthly quantities shall be totaled on an annual basis.[Basis: Cumulative Increase and Regulations 8-16-501 and 2-6-501]

Condition # 16462

For S - 3, YARD AND GREEN WASTE STOCKPILES:

~~Conditions for S-3~~

1. The total amount of yard and green waste received at S-3 shall not exceed ~~225~~ 1000 tons during any day nor 70,200 tons during any consecutive 12-month period. [Basis: Cumulative Increase]
2. The yard and green waste stockpiles shall be watered down as necessary to prevent visible dust emissions during loading or unloading. Dry, dusty material shall be watered down before unloading from truck beds as necessary to prevent visible emissions. To ensure compliance with this part, the Permit Holder shall visually observe all unloading, stockpiling, and loading operations and shall immediately initiate corrective actions if any visible dust emissions are detected. [Basis: Regulation 6-301 and Regulation 2-6-503]
- *3. Yard and green waste shall be removed from the stockpiles within 4 days of the time it is received to prevent decomposition and odors. If any stockpiles are deemed to be odorous by a District inspector, the allowable stockpile storage time shall be reduced from 4 days to 72 hours. [Basis: Regulation 1-301]
- *4. Any stockpile that is deemed to be odorous by a District inspector shall be removed within 24 hours. [Basis: Regulation 1-301]

VI. Permit Conditions

Condition # 16462

For S - 3, YARD AND GREEN WASTE STOCKPILES:

- *5. If the plant receives two or more Violation Notices from the District for "Public Nuisance" in any consecutive 12 month period, the owner/operator of this facility shall submit to the District, within 30 days, an application to modify the Permit to Operate to include the following control measures, as applicable, or any other measures that the District deems necessary and appropriate.
- a. Require the application of odor inhibitor solutions,
 - b. Reduce the allowable stockpile time, or
 - c. Discontinue use of green waste stockpiles during the ozone season or other appropriate time period.
- [Basis: Regulation 1-301]
6. In order to demonstrate compliance with Parts 1, 2 and 3, the owner/operator shall maintain the following records:
- a. Record the date, time, and amount of yard and green waste received at a stockpile.
 - b. Summarize the amount of yard and green waste received on a monthly basis.
 - c. Record the date, time, and amount of yard and green waste removed from the stockpile.
 - d. Record the date and time that water was applied to the stockpiles or associated loading or unloading operations.
- All records shall be kept on site for a minimum of 5 years from the date of entry and shall be made available to District staff upon request. [Basis: Cumulative Increase and Regulations 2-6-501 and 6-301]

VI. Permit Conditions

Condition # 17309

For S - 1, KELLER CANYON LANDFILL AND A-1 LANDFILL GAS FLARE:

~~Conditions for S-1~~

1. All landfill operations, including the acceptance and placement of waste and earthmoving and construction activities, shall be restricted to six days per week, Monday through Saturday. No operation shall take place on Sunday. [Basis: Cumulative Increase]
2. Total waste accepted and placed at the landfill shall not exceed 3,500 tons in any single day. The total cumulative amount of all wastes placed in the landfill shall not exceed 38.4 million tons. The maximum design capacity of the landfill (total volume of all wastes and cover materials placed in the landfill, excluding final cover) shall not exceed 75 million cubic yards. [Basis: Cumulative Increase and Regulation 2-1-301]
3. All waste shall be covered on a daily basis with suitable cover material meeting the requirements of the California Integrated Waste Management Board (CIWMB). This cover frequency shall be increased as necessary for the control of odors and litter. Approved daily cover materials for this site include:
 - a. Clean soil compacted to a depth of least 6 inches,
 - b. Green waste compacted to a depth of at least 6 inches, but not exceeding an average depth of 12 inches, and
 - c. Geosynthetic blankets, provided that the working face is covered with clean soil at least once a week.
 - d. Upon receiving written approval from the District, the owner/operator of S-1 may use other Alternative Daily Cover (ADC) materials that have been approved by CIWMB, provided that the use of these ADC materials do not result in odors, emission increases of any pollutant, the emission of any new pollutants, or contribute to a public nuisance. The owner/operator of S-1 shall apply for and receive an Authority to Construct before using any ADC materials that may result in odors, emission increases, the emission of any new pollutants, or that could contribute to a public nuisance.[Basis: 1-301, Cumulative Increase]
4. All on-site parking and maintenance areas for vehicles and mobile equipment shall either be paved, or provided with a gravel surface, except parking areas for landfill operation employees located directly adjacent to the working face. [Basis: Cumulative Increase]

VI. Permit Conditions

Condition # 17309

For S - 1, KELLER CANYON LANDFILL AND A-1 LANDFILL GAS FLARE:

5. All on-site roadways shall be paved, with the following exceptions:
 - a. A segment not exceeding 3,000' in length leading from the cover stockpiles to the midpoint of the working face.
 - b. A segment not exceeding 400' in length leading from the end of the main access haul road to the midpoint of the working face.
 - c. A segment not exceeding 750' in length leading from the end of the paved entrance roadway to the beginning of the unpaved 400' segment (exception b. above). This segment shall consist of a minimum of 12 inches of compacted gravel or crushed asphalt.
 - d. A segment not exceeding 1400' in length consisting of a secondary fire-access road southerly from the sedimentation basin perimeter roadway, starting from the graveled roadway surface to its southernmost point. Use of the roadway for maintenance and site patrol purposes shall not exceed an average of two vehicle trips per day.
[Basis: Cumulative Increase]
6. Speed of vehicles on unpaved roads shall not exceed 10 miles per hour. This speed limit shall be posted and enforced on unpaved roads at all times. Speed of vehicles on the fire access road shall not exceed 25 miles per hour. [Basis: Cumulative Increase]
7. All unpaved roads shall be provided with a gravel surface, excluding the fire access road, the 400 foot section of roadway from the end of the main access haul road to the working face, and the 3,000 foot scraper haul road segment from the working face to the soil stockpile area. [Basis: Cumulative Increase]
8. Operator shall control dust emissions from all unpaved roads, excluding the fire access road, by applying water as necessary and chemical dust suppressants at the following frequency and intensity:
 - a. Except as provided below, all applications of dust suppressant shall consist of 0.5 gallons per square yard of 10% MgCl₂ applied along the entire length of all unpaved roads.
 - b. Beginning May 1st and ending November 1st, dust suppressants shall be applied every 30 days.
 - c. From November 1 through May 1, dust suppressants shall be applied following any 30 consecutive dry days. For the purposes of this permit, a dry operating day shall be defined as any 24-hour period, midnight to midnight, with less than 0.09 inches of rain.

VI. Permit Conditions

Condition # 17309

For S - 1, KELLER CANYON LANDFILL AND A-1 LANDFILL GAS FLARE:

- d. Upon written request of the operator, the above dust suppression program may be modified to allow for the use of dust suppressants other than MgCl₂ provided an 85% control efficiency for TSP can be demonstrated to the satisfaction of the APCO. All such changes must be approved by the APCO in writing prior to implementation.
[Basis: Cumulative Increase]
9. Operator shall maintain a fleet of at least two water trucks at all times to wash down paved roadway surfaces and wet unpaved roads (excluding the fire access road) and work areas. [Basis: Cumulative Increase]
10. On all dry operating days, all paved and AB roads shall be completely washed down at regular intervals throughout operating hours. Rinsing frequency shall average once every fifth heavy-duty vehicle (gross weight > 5 tons) pass, excluding water trucks. Averaging shall be done on a daily basis. [Basis: Cumulative Increase]
11. On-site traffic volume of the following heavy duty vehicles shall not exceed the following number of round trips in any single day, calculated on an annual basis, except as otherwise provided in this permit:
 - a. ~~140-175~~ transfer truck trips
 - b. 4 leachate transfer truck trips
 - c. ~~50-45~~ scraper trips
 - d. For all heavy-duty vehicles, such other on-site travel as may be approved in writing by the APCO.'Annual Basis' shall be calculated by dividing the number of total truck trips by the number of operating days in any 365-day period. [Basis: Cumulative Increase]
12. For the following heavy-duty vehicles, one-way on-site trip length shall not exceed the following distances at any time during the life of the landfill except as otherwise provided by this permit:
 - a. Transfer trucks: 7,800 feet (7,400 feet paved and AB)
 - b. Leachate trucks: 3,600 feet (all paved)
 - c. Scrapers: 3,000 feet (all unpaved)A map shall be kept on site at all times identifying the paved and AB roads, clearly stating their length and the type of vehicles that use them. [Basis: Cumulative Increase]

VI. Permit Conditions

Condition # 17309

For S - 1, KELLER CANYON LANDFILL AND A-1 LANDFILL GAS FLARE:

13. On all dry operating days, all off-road soil areas, including the active face area and the active portion of the cover stockpiles, trafficked or otherwise disturbed by vehicles, equipment or operations shall be wetted down with 0.5 gallons of water per square yard or 2,420 gallons of water per acre, at least twice per day. [Basis: Cumulative Increase]
- *14. All inactive portions of the cover stockpiles shall either be covered by a latex sealer or revegetated. [Basis: CEQA, Dust Mitigation Measures]
- *15. All completed landfill phases shall be revegetated as soon as possible. [Basis: CEQA, Dust Mitigation Measures]
16. In order to demonstrate compliance with the above parts, the owner/operator of S-1 shall maintain the following records:
 - a. Daily records of the quantity of waste accepted and placed in the landfill.
 - b. Summarize the daily waste acceptance records for each calendar month.
 - c. Summarize monthly waste acceptance records for each preceding 12-month period.
 - d. For each area or cell that is not controlled by a landfill gas collection system, maintain a record of the date that waste was initially placed in the area or cell.
 - e. Record the cumulative amount of waste placed in each uncontrolled area or cell on a monthly basis.
 - f. If the Permit Holder plans to exclude an uncontrolled area or cell from the collection system requirement, the Permit Holder shall also record the types and amounts of all non-decomposable waste placed in the area and the percentage (if any) of decomposable waste placed in the area.
 - g. Record the initial operation date for each new landfill gas well and collector.
 - h. Maintain an accurate map of the landfill which indicates the locations of all refuse boundaries and the locations of all wells and collectors (using unique identifiers) that are required to be operating continuously pursuant to Part 20a. Any areas containing only non-decomposable waste shall be clearly identified. This map shall be updated at least every six months to indicate changes in refuse boundaries and to include any newly installed wells and collectors.
 - i. Daily records of the number of site trips made by heavy-duty vehicles by type of vehicle (transfer trucks, leachate trucks, scrapers, etc.)

VI. Permit Conditions

Condition # 17309

For S - 1, KELLER CANYON LANDFILL AND A-1 LANDFILL GAS FLARE:

- j. Daily records of the number of water truck rinses on paved and unpaved roads.
- k. Records of all chemical dust suppressant applications including the date of treatment, length of roads treated, and amount of dust suppressant applied.
- l. Daily records of all water applications to the working face, cover soil stockpiles, or other areas including the number of times that water was applied and the amount of water applied.

All records required to be kept under the provisions of this permit must be maintained on site for a period of five years from the date of entry, and be available for inspection by District staff upon request. [Basis: Cumulative Increase, 2-6-501]

- 17. All landfill gas collected by the gas collection well system for S-1 shall be abated at all times by ~~either the enclosed flare, A-1 or the IC Engines (S-1, S-2, or S-3) located at Plant #12101.~~ Under no circumstances shall raw landfill gas be vented to the atmosphere. This limitation does not apply to unavoidable landfill gas emissions that occur during collection system installation, maintenance, or repair performed in compliance with Regulation 8, Rule 34 Sections 113, 116, 117, or 118 or to inadvertent component or surface leaks that do not exceed the limits specified in 8-34-301.2 or 8-34-303. [Basis: 8-34-301, 8-34-303, 40 CFR 60.752(b)(2)(iii), 60.753(e), and 60.755(e)]
- 18. The landfill gas collection system described below in Part 20a shall be operated continuously. Wells shall not be shut off, disconnected, or removed from operation without prior written authorization from the District, unless the Permit Holder complies with all applicable requirements of Regulation 8, Rule 34, Sections 113, 116, 117, and 118. [Basis: 8-34-301, 40 CFR 60.753(b and c) and 60.755(e)]
- 19. Written annual reports, including drawings, shall be submitted to the District within 30 days after the permit anniversary date of the amount (in tons) of garbage placed in each uncontrolled portion of the landfill during the 12 months prior to the anniversary date. The report shall be submitted to the Permit Services Division, referenced to the above permit number, and shall include the increase (in feet) in refuse depth as well as square yardage and acreage of filled garbage in the previous 12 months. This information shall be used to re-evaluate the uncontrolled portion of the landfill for compliance with Regulation 8, Rule 34. [Basis: 8-34-301, 8-34-303, and 8-34-304]

VI. Permit Conditions

Condition # 17309

For S - 1, KELLER CANYON LANDFILL AND A-1 LANDFILL GAS FLARE:

20. Well Installation and Design Parameters:

The Permit Holder shall apply for and receive an Authority to Construct before modifying the landfill gas collection system described in Parts 20a and b below. Increasing or decreasing the number of wells or collectors or significantly changing the locations, depths or lengths of wells or collectors are all considered to be modifications that are subject to the Authority to Construct requirement.

- a. The Permit Holder has been issued a Permit to Operate for the landfill gas collection system components listed below. Well and collector locations, depths, and lengths of associated piping are as described in detail in Permit Application # 758 and # 7939.

Well Station	Number of Wells
A	12
E	12
K	12
L	6
<u>M</u>	<u>8</u>

- b. The Permit Holder has been issued an Authority to Construct for the additional landfill gas collection system components listed below. Specific well locations, depths and lengths of associated piping are as described in detail in Permit Application ~~#758~~ # 7939. Wells installed pursuant to Parts 20b shall be added to Part 20a via an administrative permit amendment in accordance with the procedures identified in Regulation 2-6-414 or 2-6-415.

Well Station	Minimum Wells	Maximum Wells
<u>L</u>	<u>0</u>	<u>4</u>
<u>F</u>	<u>0</u>	<u>11</u>
Well Station	Number of Wells	
<u>M</u>	<u>1</u>	
<u>N</u>	<u>16</u>	
<u>P</u>	<u>8</u>	

[Basis: 8-34-303, 8-34-304, 8-34-305, 40 CFR 60.755(a) and 60.759]

Conditions for A-1 Flare

21. The A-1 Flare shall be operated continuously during all times that landfill gas is being vented to the flare. [Basis: 8-34-301, 40 CFR 60.752(b)(2)(iii), 60.753(e), and 60.755(e)]

VI. Permit Conditions

Condition # 17309

For S - 1, KELLER CANYON LANDFILL AND A-1 LANDFILL GAS FLARE:

22. A temperature monitor with readout display and continuous recorder shall be installed and maintained on the flare. One or more thermocouples shall be placed in the primary combustion zone of the flare and shall accurately indicate flue gas temperature at all times. Temperature charts shall be retained for five years and made readily available to District Staff upon request. [Basis: 8-34-501, 2-6-501, 40 CFR 60.756(b)]
23. The combustion zone temperature of the flare shall be maintained at a minimum temperature of ~~1450~~-1550 degrees F, averaged over any 3-hour period. This minimum temperature shall be adjusted via an administrative permit amendment, if a source test demonstrates compliance with all applicable requirements at a different temperature. The minimum combustion zone temperature for the flare shall be equal to the average combustion zone temperature determined during the most recent complying source test minus 50 degrees F, provided that the minimum combustion zone temperature is not less than 1400 degrees F. [Basis: 8-34-301, Toxic Risk Management Policy, RACT, 40 CFR 60.758(c)(1)(i)]
24. NO_x emissions from the A-1 flare shall not exceed 14 ppmv of NO_x, expressed as NO₂ at 15% oxygen on a dry basis. [Basis: RACT, Cumulative Increase]
25. CO emissions from the A-1 flare shall not exceed 114 ppmv of CO at 15% oxygen on a dry basis. [Basis: RACT]
26. POC emissions from the A-1 flare shall not exceed 49 ppmv of POC, expressed as methane at 3% oxygen on a dry basis. Effective July 1, 2002, this limit shall be replaced by the more stringent limit listed in Part 29c. [Basis: Cumulative Increase]
27. A flow meter to measure gas flow into the flare shall be installed prior to operation and maintained in good working condition. [Basis: Cumulative Increase, 40 CFR 60.756(b)]
28. The flare shall be equipped with both local and remote alarms, automatic combustion air control, and automatic start/restart system. [Basis: 8-34-301]
29. The A-1 Landfill Gas Flare shall meet all of the following requirements:
 - a. The flare destruction efficiency of total hydrocarbons shall not be less than 98% by weight. [Basis: 8-34-301.3 and SIP 8-34-301.2]

VI. Permit Conditions

Condition # 17309

For S - 1, KELLER CANYON LANDFILL AND A-1 LANDFILL GAS FLARE:

- b. The flare destruction efficiency for total non-methane organic compounds (NMOC) shall not be less than 98% by weight unless the outlet NMOC concentration is less than 20 ppmv, expressed as hexane at 3% oxygen on a dry basis. [Basis: 40 CFR 60.752(b)(2)(iii)(B)]
 - c. Effective July 1, 2002, the flare destruction efficiency for total non-methane organic compounds (NMOC) shall not be less than 98% by weight unless the outlet NMOC concentration is less than 30 ppmv, expressed as methane at 3% oxygen on a dry basis. This subpart is not federally enforceable unless EPA approves the October 6, 1999 version of Regulation 8, Rule 34 in the SIP. [Basis: 8-34-301.3]
30. In order to demonstrate compliance with Parts 24, 25, 26 and 29, the owner/operator shall conduct a source test at A-1 once every year. The source tests shall be conducted no sooner than 9 months and no later than 12 months after the previous source test. The source test shall determine the flare outlet concentrations of oxygen, nitrogen oxides, carbon monoxide, total hydrocarbons, and non-methane hydrocarbons, and the destruction efficiencies achieved by the flare for total hydrocarbons and non-methane hydrocarbons. All test results shall be provided to the District within 45 days after testing has occurred. All source test methods used shall be subject to the prior approval of the Source Test Section of the District Technical Division. The applicant shall contact the District Source Test Section prior to performing the source test regarding the proper source test procedures and shall contact both the Source Test Section and Permit Services Division in writing 7 days prior to the source test date. [Basis: 8-34-301, RACT, 40 CFR 60.752(b)(2)(iii)]
31. A characterization of the landfill gas shall be performed concurrent with the source test required by Part 30. The characterization shall be in accordance with California Air Resources Board testing guidelines for Calderon specified air contaminants, acrylonitrile, non-methane organic compounds (NMOC), methane, carbon dioxide, oxygen, and nitrogen. The results of the characterization shall be submitted to the District within 45 days after testing has occurred. The gas sample(s) shall be drawn from the main landfill gas collection header and shall be drawn after the System has been balanced and the collection lines conditioned with landfill gas. [Basis: Toxic Risk Management Policy, 8-34-301, NSPS]

VI. Permit Conditions

Condition # 17309

For S - 1, KELLER CANYON LANDFILL AND A-1 LANDFILL GAS FLARE:

- *32. If concentrations of toxic air contaminants (TACs) are above the levels listed below, an additional risk screen run at actual concentrations will be required. Depending on the results of such screen, additional permit conditions may be required if health risks are deemed unacceptable.

Compound	Concentration (ppbv)
Acrylonitrile	100
Benzene	2700
Carbon Tetrachloride	100
Chloroform	100
Ethylene Dibromide	100
Ethylene Dichloride	300
Methylene Chloride	27600
Perchloroethylene	3600
Trichloroethylene	2300
Vinyl Chloride	1600

[Basis: Toxic Risk Management Policy]

33. The combined emissions of Precursor Organic Compounds (POC) from the S-1 Landfill and the A-1 Flare shall not exceed 46.092 tons per year (expressed as hexane). POC emissions from the landfill and flare shall be determined using the procedures and assumptions described in Parts 33a-h below. POC emissions from the landfill and flare shall be calculated at least once every five years or whenever the capacity of the landfill gas emissions control systems ~~s, (A-1 Flare, and S-1, S-2, and S-3 IC Engines at Plant #12101) are is~~ expanded, whichever is sooner.
- The current methane generation rate and uncontrolled POC emissions from the S-1 Landfill shall be calculated using the equations described in the most recent revision of AP-42 Chapter 2.4.
 - The methane generation rate shall be based on the total amount of waste accepted at the landfill to date. The Permit Holder may use either average annual or year-to-year waste acceptance rates.
 - The Permit Holder shall use the AP-42 recommended default values for the methane generation potential and methane generation rate constant. As of May 1, 2000, these default values were:
 $Lo = 100 \text{ m}^3 \text{ CH}_4/\text{Mg}$ and $k = 0.04 \text{ year}^{-1}$.

VI. Permit Conditions

Condition # 17309

For S - 1, KELLER CANYON LANDFILL AND A-1 LANDFILL GAS FLARE:

- d. When calculating uncontrolled POC emissions (UEPOC, pounds/year of POC), the Permit Holder shall use site specific NMOC, NPOC, and methane concentrations (after correcting for air infiltration) and the site specific landfill gas temperature. The site specific values shall be the average of at least three previous years of data collected pursuant to Part 31 above.
- e. Total non-methane organic compounds (NMOC) measured in the landfill gas pursuant to Part 31 may be assumed to be 100% POC, or a site specific POC concentration (CPOC) can be calculated using data from Part 33d above, where $CPOC = NMOC - NPOC$ (all concentrations expressed as methane).
- f. The fugitive POC emissions from the landfill (FEPOC, pounds/year of POC) shall be calculated using the equation below:
$$FEPOC = 0.25 * UEPOC$$
- g. POC emissions from the A-1 Flare (CEPOC, pounds/year of POC) shall be calculated using the following equation where QFLFG is the actual amount of landfill gas delivered to the flare (ft³/year), CPOC is the site specific POC concentration in the landfill gas (ppmv, after correction for air infiltration), and T is the site specific landfill gas temperature (degrees F).
$$CEPOC = 2.36 \text{ E-}6 * QFLFG * CPOC / (460+T)$$
- h. The combined POC emissions from the S-1 Landfill and A-1 Flare (TEPOC, tons/year of POC) shall be calculated using the following equation:
$$TEPOC = (FEPOC + CEPOC) / 2000$$

[Basis: Offsets]

- 34. Total reduced sulfur compounds in the collected landfill gas shall be monitored as a surrogate for monitoring sulfur dioxide in control systems exhaust. The concentration of total reduced sulfur compounds in the collected landfill gas shall not exceed 1300 ppmv (dry). In order to demonstrate compliance with this part, the Permit Holder shall measure the total sulfur content in collected landfill gas on a quarterly basis using a draeger tube. The landfill gas sample shall be taken from the main landfill gas header. The Permit Holder shall follow the manufacturer's recommended procedures for using the draeger tube and interpreting the results. The Permit Holder shall conduct the first draeger tube test no later than 3 months after the issue date of the MFR Permit and quarterly thereafter. [Basis: Regulations 9-1-302 and 2-6-503]

VI. Permit Conditions

Condition # 17309

For S - 1, KELLER CANYON LANDFILL AND A-1 LANDFILL GAS FLARE:

35. The heat input to the A-1 Flare shall not exceed 1744.8 million BTU per day or 636,852 million BTU per year. In order to demonstrate compliance with this part, the Permit Holder shall calculate and record on a monthly basis the maximum daily and total monthly heat input to the flare based on the landfill gas flow rate recorded pursuant to Part 27, the average methane concentration in the landfill gas based on the most recent source test, and a high heating value for methane of 1013 BTU/scf. The records shall be retained for five years and shall be made available to the District staff upon request. [Basis: Regulation 2-1-301]
36. The Permit Holder shall limit the quantity of VOC soil handled per day so that no more than 15 pounds of total carbon could be emitted to the atmosphere per day. VOC soil is any soil that contains volatile organic compounds, as defined in Regulation 8-40-213, at a concentration of 50 ppmw or less. Soil containing more than 50 ppmw of VOC is considered to be "contaminated soil" and is subject to Part 37 instead of Part 36. Soil containing only non-volatile hydrocarbons and meeting the requirements of Regulation 8-40-113 is not subject to Part 36. In order to demonstrate compliance with this condition, the Permit Holder shall maintain the following records in a District approved log.
- a. Record on a daily basis the amount of VOC soil handled at the landfill. This total amount (in units of pounds per day) is Q in the equation in subpart c below.
 - b. Record on a daily basis the VOC content of all soils handled at the landfill. This VOC Content (C in the equation below) should be expressed as parts per million by weight as total carbon (or C₁).
 - c. Calculate and record on a daily basis the VOC Emission Rate (E) using the following equation:
$$E = Q * C / 10^6$$
- All records shall be maintained on site or shall be made readily available to District staff upon request for at least 5 years from the date of entry.
(basis: Regulation 8-2-301)
- *37. Handling Procedures for Soil Containing Volatile Organic Compounds
- a. The procedures listed below in subparts b-l do not apply if the following criteria are satisfied. However, the record keeping requirements in subpart m below are applicable.

VI. Permit Conditions

Condition # 17309

For S - 1, KELLER CANYON LANDFILL AND A-1 LANDFILL GAS FLARE:

- i. The Permit Holder has appropriate documentation demonstrating that either the organic content of the soil or the organic concentration above the soil is below the “contaminated” level (as defined in Regulation 8, Rule 40, Sections 205, 207, and 211). The handling of soil containing VOCs in concentrations below the “contaminated” level is subject to Part 36 above.
 - ii. The Permit Holder has no documentation to prove that soil is not contaminated, but source of the soil is known and there is no reason to suspect that the soil might contain organic compounds.
- b. The Permit Holder shall provide notification to the Compliance and Enforcement Division of the Permit Holder’s intention to accept contaminated soil at the facility at least 24 hours in advance of receiving the contaminated soil. The Permit Holder shall provide an estimate of the amount of contaminated soil to be received, the degree of contamination (range and average VOC Content), and the type or source of contamination.
- c. Any soil received at the facility that is known or suspected to contain volatile organic compounds (VOCs) shall be handled as if the soil were contaminated, unless the Permit Holder receives test results proving that the soil is not contaminated. To prove that the soil is not contaminated, the Permit Holder shall collect soil samples in accordance with Regulation 8-40-601 within 24 hours of receipt of the soil by the facility. The organic content of the collected soil samples shall be determined in accordance with Regulation 8-40-602.
 - i. If these test results indicate that the soil is still contaminated or if the soil was not sampled within 24 hours of receipt by the facility, the Permit Holder must continue to handle the soil in accordance with the procedures subparts d-l below, until the soil has completed treatment or has been placed in a final disposal location and adequately covered. Storing soil in a temporary stockpile or pit is not considered treatment. Co-mingling, blending, or mixing of soil lots is not considered treatment.

VI. Permit Conditions

Condition # 17309

For S - 1, KELLER CANYON LANDFILL AND A-1 LANDFILL GAS FLARE:

- ii. If these test results indicate that the soil – as received at the facility – has an organic content of 50 ppmw or less, then the soil may be considered to be not contaminated and need not be handled in accordance with the procedures listed in subparts d-1 below, but shall be handled in accordance with Part 36 above.
- d. Any contaminated soil received at the facility shall be clearly identified as contaminated soil, shall be handled in accordance with subparts e-1 below, and shall be segregated from non-contaminated soil. Contaminated soil lots may not be co-mingled, blended, or otherwise mixed with non-contaminated soil lots prior to treatment, reuse, or disposal. Mixing soil lots in an attempt to reduce the overall concentration of the contaminated soil or to circumvent any requirements or limits is strictly prohibited.
- e. On-site handling of contaminated soil shall be limited to no more than 2 on-site transfers per soil lot. For instance, unloading soil from off-site transport vehicles into a temporary storage pile is considered one transfer. Moving soil from a temporary storage to a staging area is considered one transfer. Moving soil from a temporary storage pile to a final disposal site is considered one transfer. Moving soil from a staging area to a final disposal site is considered one transfer. Therefore, unloading soil from off-site transport into a temporary storage pile and then moving the soil from that temporary storage pile to the final disposal site is allowed. Unloading soil from off-site transport into a staging area and then moving the soil from that staging area to the final disposal site would be allowed. However, unloading soil from off-site transport to a temporary storage pile, moving this soil to a staging area, and then moving the soil again to a final disposal site would be 3 on-site transfers and is not allowed.
- f. If the contaminated soil has an organic content of less than 500 ppmw, the contaminated soil shall be either treated or deposited in a final disposal site or transported off-site for treatment, within 90 days of receipt at the facility.
- g. If the contaminated soil has an organic content 500 ppmw or more, the contaminated soil shall be either treated or deposited in a final disposal site or transported off-site for treatment, within 45 days of receipt at the facility.

VI. Permit Conditions

Condition # 17309

For S - 1, KELLER CANYON LANDFILL AND A-1 LANDFILL GAS FLARE:

- h. All active storage piles shall meet the requirements of Regulation 8-40-304 by using water sprays, vapor suppressants or approved coverings to minimize emissions. The exposed surface area of any active storage pile (including the active face at a landfill) shall be limited to 6000 ft². The types of storage piles that may become subject to these provisions include (but are not limited to) truck unloading areas, staging areas, temporary stockpiles, soil on conveyors, bulldozers or trucks, the active face of a landfill, or other permanent storage pile at the final disposal location.
- i. All inactive storage piles shall meet the requirements of Regulation 8-40-305 including the requirement to cover contaminated soil during periods of inactivity longer than one hour. The types of storage piles that may become subject to these provisions include (but are not limited to) soil on trucks or other on-site equipment, staging areas, temporary stockpiles, and the permanent storage pile at the final disposal location. District approved coverings for inactive storage piles include continuous heavy-duty plastic sheeting (in good condition, joined at the seams, and securely anchored) or encapsulating vapor suppressants (with re-treatment as necessary to prevent emissions).
- j. The Permit Holder must:
 - i. Keep contaminated soil covered with continuous heavy-duty plastic sheeting (in good condition, joined at the seams, and securely anchored) whenever soil is to be stored in temporary stockpiles or during on-site transport in trucks. Soil in trucks shall not be left uncovered for more than 1 hour.
 - ii. Establish a tipping area for contaminated soils near the active face that is isolated from the tipping area for other wastes.
 - iii. Spray contaminated soil with water or vapor suppressant immediately after dumping the soil from a truck at the tipping area.
 - iv. Ensure that all contaminated soil is transferred from the tipping area to the active face immediately after spraying with water or vapor suppressant.
 - v. Ensure that contaminated soil in the tipping area is not disturbed by subsequent trucks. Trucks shall not drive over contaminated soil in the tipping area or track contaminated soil out of the tipping area on their wheels.

VI. Permit Conditions

Condition # 17309

For S - 1, KELLER CANYON LANDFILL AND A-1 LANDFILL GAS FLARE:

- vi. Spray contaminated soil on the active face with water or vapor suppressant (to keep the soil visibly moist) until the soil can be covered with an approved covering.
- vii. Limit the area of exposed soil on the active face to no more than 6000 ft².
- viii. Ensure that contaminated soil spread on the active face is completely covered on all sides with one of the following approved coverings: at least 6 inches of clean compacted soil, at least 12 inches of compacted garbage, or at least 12 inches of compacted green waste.
- ix. Ensure that covering of soil on the active face is completed within one hour of the time that the soil was first dumped from a truck at the tipping area.

- k. Contaminated soil shall not be used as daily, intermediate, or final cover material for landfill waste operations unless the requirements of Regulation 8, Rule 40, Sections 116 or 117 have been satisfied.

- l. Contaminated soil is considered to be a decomposable solid waste pursuant to Regulation 8, Rule 34. All contaminated soil disposed of at a site shall be included in any calculations of the amount of decomposable waste in place for annual reporting requirements or for purposes of 8-34-111 or 8-34-304.

- m. The Permit Holder shall keep the following records for each lot of soil received, in order to demonstrate on-going compliance with the applicable provisions of Regulation 8, Rule 40.
 - i. For all soil received by the facility (including soil with no known contamination), record the arrival date at the facility, the soil lot number, the amount of soil in the lot, the organic content or organic concentration of the lot (if known), the type of contamination (if any), and keep copies of any test data or other information that documents whether the soil is contaminated (as defined in 8-40-205) or not contaminated, with what, and by how much.
 - ii. If the soil is tested for organic content after receipt by the facility, a report with the sampling date, test results, and the date results were received.

VI. Permit Conditions

Condition # 17309

For S - 1, KELLER CANYON LANDFILL AND A-1 LANDFILL GAS FLARE:

- iii. For all on-site handling of contaminated soil, use a checklist or other approved method to demonstrate that appropriate procedures were followed during all on-site handling activities. One checklist shall be completed for each day and for each soil lot (if multiple lots are handled per day).
- iv. For soil aerated in accordance with 8-40-116 or 117 record the soil lot number, the amount of soil in the lot, the organic content, the final placement date, the final placement location, and describe how the soil was handled or used on-site.
- v. For final disposal at a landfill, record on a daily basis the soil lot number, the amount of soil placed in the landfill, the disposal date, and the disposal location.

All records shall be retained for at least 5 years from the date of entry and shall be made available for District inspection upon request.

[Basis: Regulation 2-1-403, 8-40-301, 8-40-304 and 8-40-305]

~~38. The non-federally enforceable portions of Regulation 8, Rules 34 and 40, shall be considered federally enforceable if EPA approves the latest rules into the State Implementation Plan or into the State Plan for Municipal Solid Waste Landfills. Any rule or rule section that is replaced by a new approved rule or rule section shall be considered invalid without necessity of modifying and re-approving the permit. [Basis: Regulation 2-6-207]~~

VII. APPLICABLE LIMITS AND COMPLIANCE MONITORING REQUIREMENTS

This section has been included only to summarize the applicable emission limits contained in Section IV, Source-Specific Applicable Requirements, of this permit. The following tables show the relationship between each emission limit and the associated compliance monitoring provisions, if any. The monitoring frequency column indicates whether periodic (P) or continuous (C) monitoring is required. For periodic monitoring, the frequency of the monitoring has also been shown using the following codes: annual (A), quarterly (Q), monthly (M), weekly (W), daily (D), or on an event basis (E). No monitoring (N) has been required if the current applicable rule or regulation does not require monitoring, and the operation is unlikely to deviate from the applicable emission limit based upon the nature of the operation.

Table VII - A
Applicable Limits and Compliance Monitoring Requirements
S1 – KELLER CANYON LANDFILL

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Collection System Installation Dates	BAAQMD 8-34-304.1	<u>NY</u>		For Inactive/Closed Areas: collection system components must be installed and operating by 2 years + 60 days after initial waste placement	BAAQMD 8-34-501.7 and 501.8 and BAAQMD Condition # 17309, Part 16, subparts d-h	P/E	Records
Collection System Installation Dates	BAAQMD 8-34-304.2 and BAAQMD Condition # 17309, Part 20b	<u>NY</u>		For Active Areas: Collection system components must be installed and operating by 5 years + 60 days after initial waste placement	BAAQMD 8-34-501.7 and 501.8 and BAAQMD Condition # 17309, Part 16, subparts d-h	P/E	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - A
Applicable Limits and Compliance Monitoring Requirements
S1 – KELLER CANYON LANDFILL

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Collection System Installation Dates	BAAQMD 8-34-304.3 and BAAQMD Condition # 17309, Part 20b	N Y		For Any Uncontrolled Areas or Cells: collection system components must be installed and operating within 60 days after the uncontrolled area or cell accumulates 1,000,000 tons of decomposable waste	BAAQMD 8-34-501.7 and 501.8 and BAAQMD Condition # 17309, Part 16, subparts d-h	P/E	Records
Collection System Installation Dates	40 CFR 60.753 (a)(2) and 60.755 (b)(2)	Y		For Inactive/Closed Areas: collection system components must be installed and operating by 2 years + 60 days after initial waste placement	40 CFR 60.758(a), (d)(1) and (d)(2), and 60.759(a)(3)	P/E	Records
Collection System Installation Dates	40 CFR 60.753 (a)(1) and 60.755 (b)(1)	Y		For Active Areas: Collection system components must be installed and operating by 5 years + 60 days after initial waste placement	40 CFR 60.758(a), (d)(1) and (d)(2)	P/E	Records
Gas Flow	BAAQMD 8-34-301 and 301.1 and BAAQMD Condition # 17309, Parts 17 And 18	Y		Landfill gas collection system shall operate continuously and all collected gases shall be vented to a properly operating control system	BAAQMD Condition # 17309, Part 27	C	Gas Flow Meter and Recorder

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - A
Applicable Limits and Compliance Monitoring Requirements
S1 – KELLER CANYON LANDFILL

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Gas Flow	BAAQMD 8-34-301 and 301.1	Y		Landfill gas collection system shall operate continuously and all collected gases shall be vented to a properly operating control system	BAAQMD 8-34-501.10 and 508 (effective 7/1/02)	C	Gas Flow Meter and Recorder (every 15 minutes); effective 7/1/02
Gas Flow	SIP 8-34-301 and 301.1	Y		Landfill gas collection system shall operate continuously and all collected gases shall be vented to a properly operating control system	SIP 8-34-501.1	P/D	Operating Records
Gas Flow	40 CFR 60.753(a) and (e)	Y		Operate a Collection System in each area or cell and vent all collected gases to a properly operating control system	40 CFR 60.756(b)(2) (i or ii) and 60.758(c)(2)	C or P/M	Gas Flow Meter and Recorder (every 15 minutes) or Monthly Inspection of Bypass Valve and Lock and Records
Collection and Control Systems Shutdown Time	BAAQMD 8-34-113.2	NY		240 hours/year nor 5 consecutive days	BAAQMD 8-34-501.1	P/D	Operating Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - A
Applicable Limits and Compliance Monitoring Requirements
S1 – KELLER CANYON LANDFILL

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Collection and Control Systems Shutdown Time	SIP 8-34-113.2	Y⁺		12 hours/calendar month	SIP 8-34-501.1	P/D	Operating Records
Collection System Startup Shutdown or Malfunction	40 CFR 60.755(e)	Y		5 days per event	40 CFR 60.7(b), 60.757(f)(2) and (f)(4)	P/D	Operating Records (all occurrences and duration of each)
<u>Startup Shutdown or Malfunction Procedures</u>	<u>40 CFR 63.6(e)</u>	<u>Y</u>	<u>1/16/04</u>	<u>Minimize Emissions by Implementing SSM Plan</u>	<u>40 CFR 63.1980(a-b)</u>	<u>P/E</u>	<u>Records (all occurrences, duration of each, corrective actions)</u>
Periods of Inoperation for Parametric Monitors	BAAQMD 1-523.2	Y		15 consecutive days/incident and 30 calendar days/12 month period	BAAQMD 1-523.4	P/D	Operating Records for All Parametric Monitors
Continuous Monitors	40 CFR 60.13(e)	Y		Requires Continuous Operation except for breakdowns, repairs, calibration, and required span adjustments	40 CFR 60.7(b)	P/D	Operating Records for All Continuous Monitors
Wellhead Pressure	BAAQMD 8-34-305.1	<u>NY</u>	<u>7/1/02</u>	< 0 psig	BAAQMD 8-34-414, 501.9 and 505.1	P/M	Monthly Inspection and Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - A
Applicable Limits and Compliance Monitoring Requirements
S1 – KELLER CANYON LANDFILL

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Wellhead Pressure	40 CFR 60.753(b)	Y		< 0 psig	40 CFR 60.755(a)(3), 60.756(a)(1), and 60.758(c) and (e)	P/M	Monthly Inspection and Records
Temperature of Gas at Wellhead	BAAQMD 8-34-305.2	NY	7/1/02	< 55 °C	BAAQMD 8-34-414, 501.9 and 505.2	P/M	Monthly Inspection and Records
Temperature of Gas at Wellhead	40 CFR 60.753(c)	Y		< 55 °C	40 CFR 60.755(a)(5), 60.756(a)(3), and 60.758(c) and (e)	P/M	Monthly Inspection and Records
Gas Concentrations at Wellhead	BAAQMD 8-34-305.3 or 305.4	NY	7/1/02	N ₂ < 20% OR O ₂ < 5%	BAAQMD 8-34-414, 501.9 and 505.3 or 505.4	P/M	Monthly Inspection and Records
Gas Concentrations at Wellhead	40 CFR 60.753(c)	Y		N ₂ < 20% OR O ₂ < 5%	40 CFR 60.755(a)(5), 60.756(a)(2), and 60.758(c) and (e)	P/M	Monthly Inspection and Records
Well Shutdown Limits	BAAQMD 8-34-116.2	NY		No more than 5 wells at a time or 10% of total collection system, whichever is less	BAAQMD 8-34-116.5 and 501.1	P/D	Records
Well Shutdown Limits	BAAQMD 8-34-116.3	NY		24 hours per well	BAAQMD 8-34-116.5 and 501.1	P/D	Records
Well Shutdown Limits	BAAQMD 8-34-117.4	NY		No more than 5 wells at a time or 10% of total collection system, whichever is less	BAAQMD 8-34-117.6 and 501.1	P/D	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - A
Applicable Limits and Compliance Monitoring Requirements
S1 – KELLER CANYON LANDFILL

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Well Shutdown Limits	BAAQMD 8-34-117.5	NY		24 hours per well	BAAQMD 8-34-117.6 and 501.1	P/D	Records
TOC (Total Organic Compounds Plus Methane)	BAAQMD 8-34-301.2	NY		1000 ppmv as methane (component leak limit)	BAAQMD 8-34-501.6 and 503	P/Q	Quarterly Inspection of collection and control system components with OVA and Records
TOC	SIP 8-34-301.1	Y		1000 ppmv as methane (component leak limit)	SIP 8-34-503	P/Q	Quarterly Inspection with OVA
TOC	BAAQMD 8-34-303a	Y	Expires 7/1/02	1000 ppmv as methane at 3 inches above surface		N	
TOC	BAAQMD 8-34-303b	NY	7/1/02	500 ppmv as methane at 2 inches above surface	BAAQMD 8-34-415, 416, 501.6, 506 and 510	P/M, Q, and E	Monthly Visual Inspection of Cover, Quarterly Inspection with OVA of Surface, Various Reinspection Times for Leaking Areas, and Records
TOC	SIP 8-34-303	Y⁺		1000 ppmv as methane at 3 inches above surface		N	

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - A
Applicable Limits and Compliance Monitoring Requirements
S1 – KELLER CANYON LANDFILL

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
TOC	40 CFR 60.753(d)	Y		<500 ppmv as methane at 5-10 cm from surface	40 CFR 60.755(c)(1), (4) and (5), 60.756(f), and 60.758(c) and (e)	P/M, Q and E	Monthly Visual Inspection of Cover, Quarterly Inspection with OVA of Surface, Various Reinspection Times for Leaking Areas, and Records
POC	BAAQMD Condition # 17309, Part 33	Y		46.092 tons per year (from landfill and flare combined)	BAAQMD Condition # 17309, Part 33	P/E	Calculation Procedure (once every 5 years)
Total Carbon	BAAQMD 8-2-301	Y		15 pounds/day or 300 ppm, dry basis only for aeration of or use as cover soil of soil containing \leq 50 ppmw of volatile organic compounds	BAAQMD Condition # 17309, Part 36a-c	P/E	Records
Amount of Contaminated Soil Aerated or Used as Cover	BAAQMD 8-40-116.1	NY		1 cubic yard per project	BAAQMD Condition # 17309, Parts 36a-c and 37m	P/E	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - A
Applicable Limits and Compliance Monitoring Requirements
S1 – KELLER CANYON LANDFILL

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Amount of Contaminated Soil Aerated or Used as Cover	BAAQMD 8-40-116.2	<u>NY</u>		8 cubic yards per project, provided organic content ≤ 500 ppmw and limited to 1 exempt project per 3 month period	BAAQMD 8-40-116.2 and BAAQMD Condition # 17309, Parts 36a-c and 37m	P/E	Records
Amount of Accidental Spillage	BAAQMD 8-40-117	<u>NY</u>		Soil Contaminated by Accidental Spillage of ≤ 5 gallons of Liquid Organic Compounds	<u>None</u>	N	<u>NA</u>
Total Aeration Project Emissions	BAAQMD 8-40-118	<u>NY</u>		150 pounds per project and toxic air contaminant emissions per year <BAAQMD Table 2-1-316 limits	BAAQMD Condition # 17309, Part 37m	P/E	Records
Amount of Contaminated Soil Aerated or Used as Cover	BAAQMD 8-40-301 and BAAQMD Condition # 17309, Part 37k	<u>NY</u>		Prohibited for Soil with Organic Content >50 ppmw unless exempt per BAAQMD 8-40-116, 117, or 118	BAAQMD Condition # 17309, Parts 36a-c and 37m	P/E	Records
Amount of Contaminated Soil Aerated or Used as Cover	<u>SIP</u> <u>8-40-301</u>	<u>Y⁺</u>		<u>Organic Content — Amount</u> <u>—ppmw — yd³/day</u> <u>—50-99 — 600</u> <u>—100-499 — 120</u> <u>—500-999 — 60</u> <u>—1000-1999 — 30</u> <u>—2000-2999 — 15</u> <u>—3000-3999 — 10</u> <u>—4000-4999 — 8</u> <u>—5000+ — 0.1</u>	<u>BAAQMD</u> <u>Condition #</u> <u>17309, Parts</u> <u>36a-c and</u> <u>37m.</u>	<u>P/E</u>	<u>Records</u>

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - A
Applicable Limits and Compliance Monitoring Requirements
S1 – KELLER CANYON LANDFILL

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Contaminated Soil Handling	BAAQMD Condition # 17309, Part 37e	NY		Limited to 2 on-site transfers per lot of contaminated soil	BAAQMD Condition # 17309, Part 37m	P/E	Records
Contaminated Soil On-Site Storage Time	BAAQMD Condition # 17309, Part 37f-g	NY		If organic content is: < 500 ppmw, storage time ≤ 90 days; If organic content is: ≥ 500 ppmw, storage time ≤ 45 days	BAAQMD Condition # 17309, Part 37m	P/E	Records
H ₂ S	BAAQMD 9-2-301	N		Property Line ground level limits ≤ 0.06 ppm Averaged over 3 minutes and ≤ 0.03 ppm Averaged over 60 minutes	None	N	NA
Total Sulfur Content in Landfill Gas	BAAQMD Condition # 17309, Part 34.	Y		Total Sulfur Content ≤ 1300 ppmv (dry)	BAAQMD Condition # 17309, Part 34.	P/Q	Sulfur Analysis of landfill gas only
Opacity	BAAQMD 6-301	Y		Ringelmann No. 1 for 3 minutes in any hour	BAAQMD Condition # 17309, Part 16j-l	P/D	Records of Water and Dust Suppressant Application
Lead	BAAQMD 11-1-302	Y		Ground level concentration ≤ 1.0 µg/m ³ averaged over 24 hours	None	N	NA
Beryllium	BAAQMD 11-3-301 or 303	N		10 grams / 24 hours or 0.01 µg/m ³ averaged over 30 days	None	N	NA

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - A
Applicable Limits and Compliance Monitoring Requirements
S1 – KELLER CANYON LANDFILL

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Serpentine Material	BAAQMD 11-14-301	N		Surfacing Material \leq 5% asbestos	BAAQMD 11-14-501	P/D	Records of Testing and Receipts
Operating Time	BAAQMD Condition # 17309, Part 1	Y		Monday through Friday	BAAQMD Condition # 17309, Part 16a, i	P/D	Records of Waste Received and Truck Traffic
Waste Received	BAAQMD Condition # 17309, Part 2	Y		3500 tons per day	BAAQMD Condition # 17309, Part 16a	P/D	Records of Waste Received
Cumulative Waste In-Place	BAAQMD Condition # 17309, Part 2	Y		38.4 million tons (34.8 million Mg)	BAAQMD Condition # 17309, Part 16a	P/D	Records of Waste Placed in Landfill
Design Capacity	BAAQMD Condition # 17309, Part 2	Y		75 million yd ³ (57.3 million m ³) of all wastes and cover materials (excluding final cover)	BAAQMD Condition # 17309, Parts 16a, 36a, and 37m	P/D	Records of Materials Placed in Landfill
Unpaved Road Length	BAAQMD Condition # 17309, Part 5a	Y		3000 feet from cover stockpile to working face midpoint	BAAQMD Condition # 17309, Part 12	P/E	Site Maps
Unpaved Road Length	BAAQMD Condition # 17309, Part 5b	Y		400 feet from end of main access road to working face midpoint	BAAQMD Condition # 17309, Part 12	P/E	Site Maps
Unpaved Road Length	BAAQMD Condition # 17309, Part 5c	Y		750 feet from end of paved road to end of main access road (this section must have 12 inches of gravel or crushed asphalt)	BAAQMD Condition # 17309, Part 12	P/E	Site Maps

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - A
Applicable Limits and Compliance Monitoring Requirements
S1 – KELLER CANYON LANDFILL

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Unpaved Road Length	BAAQMD Condition # 17309, Part 5d	Y		1400 feet of fire access roads	BAAQMD Condition # 17309, Part 12	P/E	Site Maps
Vehicle Speed	BAAQMD Condition # 17309, Part 6	Y		10 mph on unpaved roads and 25 mph on fire access roads	BAAQMD Condition # 17309, Part 6	P/E	Posted Signs and Enforcement if Necessary
Dust Suppress-ant Application Rate for Unpaved Roads	BAAQMD Condition # 17309, Part 8a-c	Y		0.5 gallons per square yard of 10% magnesium chloride applied once every 30 days between May 1 and November 1 and once every 30 consecutive dry days between November 1 and May 1	BAAQMD Condition # 17309, Part 16k	P/D	Records
Water Application Rate for Roads	BAAQMD Condition # 17309, Parts 8 and 10	Y		Once every fifth heavy duty vehicle and more often as necessary	BAAQMD Condition # 17309, Part 16i-j	P/D	Records
Water Applicati on Rate for Active face and Soil Areas	BAAQMD Condition # 17309, Part 13	Y		0.5 gallons per square yard twice per day on all dry days	BAAQMD Condition # 17309, Part 16 ₁	P/D	Records
Truck Traffic Volume	BAAQMD Condition # 17309, Part 11a	Y		140-175 transfer truck trips per annual average day	BAAQMD Condition # 17309, Part 16i	P/D	Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - A
Applicable Limits and Compliance Monitoring Requirements
S1 – KELLER CANYON LANDFILL

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Truck Traffic Volume	BAAQMD Condition # 17309, Part 11b	Y		4 leachate truck trips per annual average day	BAAQMD Condition # 17309, Part 16i	P/D	Records
Truck Traffic Volume	BAAQMD Condition # 17309, Part 11c	Y		50-45 scraper trips per annual average day	BAAQMD Condition # 17309, Part 16i	P/D	Records
Truck Traffic Trip Length	BAAQMD Condition # 17309, Part 12a	Y		7800 feet for transfer trucks	BAAQMD Condition # 17309, Part 12	P/E	Site Maps and Records
Truck Traffic Trip Length	BAAQMD Condition # 17309, Part 12b	Y		3600 feet for leachate trucks	BAAQMD Condition # 17309, Part 12	P/E	Site Maps and Records
Truck Traffic Trip Length	BAAQMD Condition # 17309, Part 12c	Y		3000 feet for scrapers	BAAQMD Condition # 17309, Part 12	P/E	Site Maps and Records
Acrylonitrile	BAAQMD Condition # 17309, Part 32	N		100 ppbv	BAAQMD Condition # 17309, Part 31	P/A	Annual Source Test
Benzene	BAAQMD Condition # 17309, Part 32	N		2,700 ppbv	BAAQMD Condition # 17309, Part 31	P/A	Annual Source Test
Carbon Tetra-chloride	BAAQMD Condition # 17309, Part 32	N		100 ppbv	BAAQMD Condition # 17309, Part 31	P/A	Annual Source Test

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - A
Applicable Limits and Compliance Monitoring Requirements
S1 – KELLER CANYON LANDFILL

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Chloroform	BAAQMD Condition # 17309, Part 32	N		100 ppbv	BAAQMD Condition # 17309, Part 31	P/A	Annual Source Test
Ethylene Dibromide	BAAQMD Condition # 17309, Part 32	N		100 ppbv	BAAQMD Condition # 17309, Part 31	P/A	Annual Source Test
Ethylene Dichloride	BAAQMD Condition # 17309, Part 32	N		300 ppbv	BAAQMD Condition # 17309, Part 31	P/A	Annual Source Test
Methylene Chloride	BAAQMD Condition # 17309, Part 32	N		27,600 ppbv	BAAQMD Condition # 17309, Part 31	P/A	Annual Source Test
Perchloroethylene	BAAQMD Condition # 17309, Part 32	N		3,600 ppbv	BAAQMD Condition # 17309, Part 31	P/A	Annual Source Test
Trichloroethylene	BAAQMD Condition # 17309, Part 32	N		2,300 ppbv	BAAQMD Condition # 17309, Part 31	P/A	Annual Source Test
Vinyl Chloride	BAAQMD Condition # 17309, Part 32	N		1,600 ppbv	BAAQMD Condition # 17309, Part 31	P/A	Annual Source Test

~~1 This section has been removed from BAAQMD Regulations because it has been superseded. Nevertheless, the source must comply with this regulation until US EPA has reviewed and approved (or disapproved) the District's revision of the regulation.~~

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – B
Applicable Limits and Compliance Monitoring Requirements
S2 – WIPE CLEANING OPERATION

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Solvent Usage	BAAQMD Condition # 9527, Part 1	Y		0.75 gallons per day and 100 gallons per 12-month period	BAAQMD Condition # 9527, Part 2	P/M	Records
					BAAQMD 8-16-501.2	P/A	Records
					SIP 8-16-501.2 ¹	P/Q	Records

- ¹ This section has been removed from BAAQMD Regulations because it has been superseded. Nevertheless, the source must comply with this regulation until US EPA has reviewed and approved (or disapproved) the District's revision of the regulation.

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – C
Applicable Limits and Compliance Monitoring Requirements
S3 – YARD AND GREEN WASTE STOCKPILES

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD 6-301	Y		Ringelmann No. 1	BAAQMD Condition # 16462, Part 2	C	Visual Observation of Source in Operation
Waste Received	BAAQMD Condition # 16462, Part 1	Y		225 tons per day and 70,200 tons per 12-month period	BAAQMD Condition # 16462, Part 6a and b	P/E	Records of Amount of Waste Received
Waste Storage Time	BAAQMD Condition # 16462, Part 3	N		4 days from receipt of waste	BAAQMD Condition # 16462, Part 6a and c	P/E	Records of Date and Time for Waste Receipt and Processing
Odorous Stockpile Storage Time	BAAQMD Condition # 16462, Part 4	N		24 hours from the time the stockpile is deemed “odorous”	BAAQMD Condition # 16462, Part 6a and c	P/E	Records of Date and Time for Waste Receipt and Processing

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – D
Applicable Limits and Compliance Monitoring Requirements
A1 – LANDFILL GAS FLARE

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Heat Input	BAAQMD Condition # 17309, Part 35	Y		≤ 1744.8 MM BTU per day and ≤ 636,852 MM BTU per year	BAAQMD Condition # 17309, Part 35	P/M	Records
Gas Flow	BAAQMD 8-34-301, 301.1, and 301.3 and BAAQMD Condition # 17309, Parts 17 and 21	Y		Vent all collected gases to a properly operating control system and operate control system continuously.	BAAQMD Condition # 17309, Parts 27 And 28	C	Gas Flow Meter and Alarms
Gas Flow	BAAQMD 8-34-301, 301.1, and 301.3 and BAAQMD Condition # 17309, Parts 17 And 21	Y		Vent all collected gases to a properly operating control system and operate control system continuously.	BAAQMD 8-34-501.10 and 508 (effective 7/1/02) and BAAQMD Condition # 17309, Parts 27 and 28	C	Gas Flow Meter and Recorder (every 15 minutes); Records and Alarm effective 7/1/02
Gas Flow	SIP 8-34-301, 301.2, and 301.4	Y		Vent all collected gases to a properly operating control system and operate control system continuously.	SIP 8-34-501.2 and BAAQMD Condition # 17309, Parts 27, And 28	P/D	Operating Records, Flow Meter, and Alarms

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – D
Applicable Limits and Compliance Monitoring Requirements
A1 – LANDFILL GAS FLARE

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Gas Flow	40 CFR 60.752 (b)(2)(iii) and 60.753(e) and (f)	Y		Vent all collected gases to a properly operating control system and operate control system at all times when gas is vented to it	40 CFR 60.756(b)(2) (i or ii) and 60.758(c)(2)	C or P/M	Gas Flow Meter and Recorder (every 15 minutes) or Monthly Inspection of Bypass Valve and Lock and Records
Collection and Control Systems Shutdown Time	BAAQMD 8-34-113.2	N Y		240 hours/year	BAAQMD 8-34-501.2	P/D	Operating Records
Collection and Control Systems Shutdown Time	SIP 8-34-113.2	Y ⁺		12 hours/calendar month	SIP 8-34-501.2	P/D	Operating Records
Control System Startup Shutdown or Mal-function	40 CFR 60.755(e)	Y		1 hour per event	40 CFR 60.7(b), 60.757(f)(2) and (f)(3)	P/D	Operating Records (all occurrences and duration of each)
<u>Startup Shutdown or Mal-function Pro-cedures</u>	<u>40 CFR 63.6(e)</u>	<u>Y</u>	<u>1/16/04</u>	<u>Minimize Emissions by Implementing SSM Plan</u>	<u>40 CFR 63.1980(a-b)</u>	<u>P/E</u>	<u>Records (all occurrences, duration of each, corrective actions)</u>

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – D
Applicable Limits and Compliance Monitoring Requirements
A1 – LANDFILL GAS FLARE

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
TOC	BAAQMD 8-34-301.3a and BAAQMD Condition #17309, Part 29.a.	N	Expires 7/1/02	98% removal by weight	BAAQMD Condition # 17309, Parts 30. And 31.	P/A	Annual Source Test
TOC	SIP 8-34-301.2 and BAAQMD Condition #17309, Part 29.a.	Y		98% removal by weight	BAAQMD Condition # 17309, Parts 30. And 31.	P/A	Annual Source Test
Non-Methane Organic Compounds (NMOC)	BAAQMD 8-34-301.3b and BAAQMD Condition # 17309, Part 29c	NY	7/1/02	98% removal by weight OR < 30 ppmv dry @ 3% O ₂ , expressed as methane	BAAQMD 8-34-412 and <u>8-34-501.4 and</u> BAAQMD Condition # 17309, Parts 30 And 31	P/A	Initial and Annual Source Tests
NMOC	40 CFR 60.752(b) (2)(iii)(B) and BAAQMD Condition # 17309, Part 29b	Y		98% removal by weight OR < 20 ppmv dry @ 3% O ₂ , expressed as hexane	40 CFR 60.8 and 60.752(b) (2)(iii)(B) and 60.758 (b)(2)(ii)	P/E	Initial Source Test and Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – D
Applicable Limits and Compliance Monitoring Requirements
A1 – LANDFILL GAS FLARE

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
POC	BAAQMD Condition # 17309, Part 26	Y	Expired ds 7/1/02 (expira-tion date not FE)	49 ppmv of NO _x , expressed as NO ₂ at 15% O ₂ , dry	BAAQMD Condition # 17309, Part 30	P/A	Annual Source Test
POC	BAAQMD Condition # 17309, Part 33	Y		46.092 tons per year (from landfill and flare combined)	BAAQMD Condition # 17309, Part 33	P/E	Calculation Procedure (once every 5 years)
Temperature of Combustion Zone (CT)	BAAQMD Condition # 17309, Part 23	Y		CT \geq 4450-1550 °F (3-hour average)	BAAQMD 8-34-501.3 and 507, SIP 8-34-501.3 and BAAQMD Condition # 17309, Part 22-	C	Temperature Sensor and Recorder (continuous)
Temperature of Combustion Zone (CT)	40 CFR 60.758 (c)(1)(i)	Y		CT \geq 4450-1550 °F (3-hour average) from (CT \geq CT _{PF} – 28 °C), where CT _{PF} is the average combustion temperature during the most recent complying performance test, CT _{PF} was 1500-1600 °F on 11/6/00 <u>10/30/02</u>	40 CFR 60.756(b)(1) and 60.758 (b)(2)(i)	C	Temperature Sensor and Recorder (measured every 15 minutes and averaged over performance test time period and 3-hours)
TOC (Total Organic Compounds Plus Methane)	BAAQMD 8-34-301.2	NY		1000 ppmv as methane (component leak limit)	BAAQMD 8-34-501.6 and 503	P/Q	Quarterly Inspection of collection and control system components with OVA and Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – D
Applicable Limits and Compliance Monitoring Requirements
A1 – LANDFILL GAS FLARE

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
TOC	SIP 8-34-301.1	N		1000 ppmv as methane (component leak limit)	SIP 8-34-503	P/Q	Quarterly Inspection with OVA
Opacity	BAAQMD 6-301	Y		Ringelmann No. 1	BAAQMD 8-34-501.3 and 507, SIP 8-34-501.3 and BAAQMD Condition # 17309, Part 22	C	Temperature Sensor and Recorder (continuous)
FP	BAAQMD 6-310	Y		0.15 grains/dscf		N	
SO ₂	BAAQMD 9-1-301	Y		Property Line Ground Level Limits ≤ 0.5 ppm for 3 minutes, ≤ 0.25 ppm for 60 minutes, and ≤ 0.05 ppm for 24 hours		N	
SO ₂	BAAQMD 9-1-302	Y		≤ 300 ppm (dry)	BAAQMD Condition # 17309, Part 34	P/Q	Sulfur Analysis of landfill gas only
H ₂ S	BAAQMD 9-2-301	N		Property Line ground level limits ≤ 0.06 ppm Averaged over 3 minutes and ≤ 0.03 ppm Averaged over 60 minutes		N	

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – D
Applicable Limits and Compliance Monitoring Requirements
A1 – LANDFILL GAS FLARE

Type of Limit	Citation of Limit	FE Y/N	Future Effective Date	Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Total Sulfur Content in Land-fill Gas	BAAQMD Condition # 17309, Part 34	Y		Total Sulfur Content \leq 1300 ppmv (dry)	BAAQMD Condition # 17309, Part 34	P/Q	Sulfur Analysis of landfill gas only
NO _x	BAAQMD Condition # 17309, Part 24	Y		14 ppmv of NO _x , expressed as NO ₂ at 15% O ₂ , dry	BAAQMD Condition # 17309, Part 30	P/A	Annual Source Test
CO	BAAQMD Condition # 17309, Part 25	Y		114 ppmv of CO at 15% O ₂ , dry	BAAQMD Condition # 17309, Part 30	P/A	Annual Source Test
Periods of Inoperation for Parametric Monitors	BAAQMD 1-523.2	Y		15 consecutive days/incident and 30 calendar days/12 month period	BAAQMD 1-523.4	P/D	Operating Records for All Parametric Monitors
Continuous Monitors	40 CFR 60.13(e)	Y		Requires Continuous Operation except for breakdowns, repairs, calibration, and span adjustments	40 CFR 60.7(b)	P/D	Operating Records for All Continuous Monitors

~~1— This section has been removed from BAAQMD Regulations because it has been superseded. Nevertheless, the source must comply with this regulation until US EPA has reviewed and approved (or disapproved) the District's revision of the regulation.~~

VIII. TEST METHODS

The test methods associated with the emission limit of a District regulation are generally referenced in Section 600 et seq. of the regulation. The following table indicates only the test methods associated with the emission limits referenced in Section VII, Applicable Emission Limits & Compliance Monitoring Requirements, of this permit.

Table VIII
Test Methods

Applicable Requirement	Description of Requirement	Acceptable Test Methods
BAAQMD 6-301	Ringelmann No. 1 Limitation	Manual of Procedures, Volume I, Evaluation of Visible Emissions
BAAQMD 6-310	Particulate Weight Limitation	Manual of Procedures, Volume IV, ST-15, Particulate; or EPA Reference Method 5 Determination of Particulate Matter Emissions from Stationary Sources for combustion sources
BAAQMD 8-2-301	Miscellaneous Operations	Manual of Procedures, Volume IV, ST-7, Organic Compounds; or EPA Reference Method 25 or 25A
BAAQMD 8-34-301.2	Collection and Control System Leak Limitations	EPA Reference Method 21, Determination of Volatile Organic Compound Leaks
BAAQMD 8-34-301.3	Limits for Flares	Manual of Procedures, Volume IV, ST-7, Organic Compounds and ST-14, Oxygen, Continuous Sampling; or EPA Reference Method 18, 25, 25A, or 25C
BAAQMD 8-34-303	Landfill Surface Requirements	EPA Reference Method 21, Determination of Volatile Organic Compound Leaks
BAAQMD 8-34-305.1	Wellhead Gauge Pressure	APCO Approved Device
BAAQMD 8-34-305.2	Wellhead Temperature	APCO Approved Device
BAAQMD 8-34-305.3	Wellhead Nitrogen	EPA Reference Method 3C, Determination of Carbon Dioxide, Methane, Nitrogen, and Oxygen from Stationary Sources
BAAQMD 8-34-305.4	Wellhead Oxygen	EPA Reference Method 3C, Determination of Carbon Dioxide, Methane, Nitrogen, and Oxygen from Stationary Sources
BAAQMD 8-34-412	Compliance Demonstration Test	EPA Reference Method 18, Measurement of Gaseous Organic Compound Emissions by Gas Chromatography, Method 25, Determination of Total Gaseous Nonmethane Organic Emissions as Carbon, Method 25A, Determination of Total Gaseous Organic Concentration Using a Flame Ionization Analyzer, or Method 25C, Determination of Nonmethane Organic Compounds (NMOC) in MSW Landfill Gases
SIP 8-34-301.1	Collection and Control Systems Leak Limitations	EPA Reference Method 21, Determination of Volatile Organic Compound Leaks

VIII. Test Methods

**Table VIII
Test Methods**

Applicable Requirement	Description of Requirement	Acceptable Test Methods
SIP 8-34-301.2⁺	Flare Limit	Manual of Procedures, Volume IV, ST 7, Organic Compounds; or EPA Reference Method 25 or 25A
SIP 8-34-303	Landfill Surface Requirements	EPA Reference Method 21, Determination of Volatile Organic Compound Leaks
BAAQMD 8-40-116.2	Organic Content Limit for Small Volume Exemption	BAAQMD 8-40-601 and EPA Reference Methods 8015B and 8021B
BAAQMD 8-40-301	Limits on Uncontrolled Aeration of Contaminated Soil	BAAQMD 8-40-601 and EPA Reference Methods 8015B and 8021B; or EPA Reference Method 21
SIP 8-40-301⁺	Limits on Uncontrolled Aeration of Contaminated Soil	BAAQMD 8-40-601 and EPA Reference Methods 8010 or 8015
BAAQMD 9-1-301	Limitations on Ground Level Concentrations (SO ₂)	Manual of Procedures, Volume VI, Part 1, Ground Level Monitoring for Hydrogen Sulfide and Sulfur Dioxide
BAAQMD 9-1-302	General Emission Limitation (SO ₂)	Manual of Procedures, Volume IV, ST-19A, Sulfur Dioxide, Continuous Sampling, or ST-19B, Total Sulfur Oxides, Integrated Sample
BAAQMD 9-2-301	Limitations on Hydrogen Sulfide	Manual of Procedures, Volume VI, Part 1, Ground Level Monitoring for Hydrogen Sulfide and Sulfur Dioxide
BAAQMD 11-1-302	Ground Level Concentration Limit Without Background (lead)	Manual of Procedures, Volume VI, Part 2, Atmospheric Sampling of Ground Level Lead Concentrations, Sections 2.1 General and 2.2 Mass Emission Limitations
BAAQMD 11-3-301	Emission Limitation (beryllium)	Test waste in accordance with EPA SW-846 and calculate emissions in accordance with EPA AP-42
BAAQMD 11-14-301	Prohibition of Use for Surfacing Operations (asbestos serpentine)	ARB Test Method 435, Determination of Asbestos Content of Serpentine Aggregate
40 CFR 60.8	Performance Tests	EPA Reference Method 18, Measurement of Gaseous Organic Compound Emissions by Gas Chromatography, Method 25, Determination of Total Gaseous Nonmethane Organic Emissions as Carbon, Method 25A, Determination of Total Gaseous Organic Concentration Using a Flame Ionization Analyzer, or Method 25C, Determination of Nonmethane Organic Compounds (NMOC) in MSW Landfill Gases

VIII. Test Methods

Table VIII
Test Methods

Applicable Requirement	Description of Requirement	Acceptable Test Methods
40 CFR 60.752 (b)(2)(iii)(B)	NMOC Outlet Concentration and Destruction Efficiency Limits	EPA Reference Method 18, Measurement of Gaseous Organic Compound Emissions by Gas Chromatography, Method 25, Determination of Total Gaseous Nonmethane Organic Emissions as Carbon, Method 25A, Determination of Total Gaseous Organic Concentration Using a Flame Ionization Analyzer, or Method 25C, Determination of Nonmethane Organic Compounds (NMOC) in MSW Landfill Gases
40 CFR 60.753(b)	Wellhead Pressure	APCO Approved Device
40 CFR 60.753(c)	Temperature, N ₂ , and O ₂ concentration in wellhead gas	EPA Reference Method 3C, Determination of Carbon Dioxide, Methane, Nitrogen, and Oxygen from Stationary Sources
40 CFR 60.753(d)	Methane Limit at Landfill Surface	EPA Reference Method 21, Determination of Volatile Organic Compound Leaks
BAAQMD Condition # 17309		
BAAQMD Condition # 17309 , Part 23	Flare Combustion Temperature Limit	APCO Approved Device
BAAQMD Condition # 17309 , Part 24	NO _x Limit	Manual of Procedures, Volume IV, Oxides of Nitrogen, Continuous Sampling, and ST-14, Oxygen, Continuous Sampling; or EPA Reference Method 20
BAAQMD Condition # 17309 , Part 25	CO Limit	Manual of Procedures, Volume IV, ST-6, Carbon Monoxide, Continuous Sampling, and ST-14, Oxygen, Continuous Sampling; or EPA Reference Method 10
BAAQMD Condition # 17309 , Part 26	POC Limit	Manual of Procedures, Volume IV, ST-14, Oxygen, Continuous Sampling, and either Manual of Procedures, Volume IV, ST-7, Organic Compounds; or EPA Reference Method 18, 25, 25A, or 25C
BAAQMD Condition # 17309 , Part 29a	Total Hydrocarbon Destruction Efficiency Limit	Manual of Procedures, Volume IV, ST-7, Organic Compounds and ST-14, Oxygen, Continuous Sampling; or EPA Reference Method 18, 25, 25A, or 25C

VIII. Test Methods

**Table VIII
Test Methods**

Applicable Requirement	Description of Requirement	Acceptable Test Methods
BAAQMD Condition # 17309 , Part 29b-c	NMOC Destruction Efficiency Limit and NMOC Outlet Concentration Limit	Manual of Procedures, Volume IV, ST-7, Organic Compounds and ST-14, Oxygen, Continuous Sampling; or EPA Reference Method 18, 25, 25A, or 25C
BAAQMD Condition # 17309 , Part 32	Limits for Specified Toxic Air Contaminants (Acrylonitrile, Benzene, Carbon Tetrachloride, Ethylene Dibromide, Ethylene Dichloride, Methylene Chloride, Perchloroethylene, Trichloroethylene, and Vinyl Chloride) in Landfill Gas	EPA Reference Method 18, Measurement of Gaseous Organic Compound Emissions by Gas Chromatography
BAAQMD Condition # 17309 , Part 33	POC Emissions Limit for Landfill and Flare	Calculation Procedure Described in BAAQMD Condition # 17309, Part 33a-h
BAAQMD Condition # 17309 , Part 34	Limit for Total Reduced Sulfur Compounds in Landfill Gas	Draeger Tube: used in accordance with manufacturer's recommended procedures.
BAAQMD Condition # 17309 , Part 35	Heat Input Limit for Flare	APCO approved calculation procedure as described in BAAQMD Condition # 17309, Part 35
BAAQMD Condition # 17309 , Part 36	Total Carbon Emission Limit for Use or Disposal of Soil Containing VOCs	VOC Content as determined by EPA Reference Methods 8015B, 8021B (or any method determined to be equivalent by the US EPA and approved by the APCO) and converted to Total Carbon as defined in BAAQMD Regulation 8-2-202. Total Carbon Emissions determined by APCO approved equation described in BAAQMD Condition #17309, Part 36c
BAAQMD Condition # 17309 , Part 37, subparts a-m	Handling Procedures for Soil Containing Volatile Organic Compounds	EPA Reference Methods 8015B, 8021B, or any method determined to be equivalent by the US EPA and approved by the APCO

~~1 — This section has been removed from BAAQMD Regulations because it has been superseded. Nevertheless, the source must comply with this regulation until US EPA has reviewed and approved (or disapproved) the District's revision of the regulation.~~

IX. PERMIT SHIELD

Not Applicable

X. REVISION HISTORY

Initial Proposal: February 21, 2001

Title V Permit Issuance: September 20, 2001

Minor Revision: [insert approval date]

- Add and revise text in Section I, III, IV and VII to conform to current standard text.
- Correct and update regulatory dates in Sections I. and III. Include additional applicable requirement citations in Section III.
- Update Table II A to reflect expansion of the landfill gas collection system.
- Update Table II B to conform to data presented for other landfill flares.
- Update minimum combustion zone temperature, in Tables II-B and VII-D, and Condition #17309 Part 23, to reflect the calculated minimum based on the most recent complying performance test (October 30, 2002).
- Updates Tables IV-A, IV-B, IV-D, VII-A, VII-B, VII-D, and VIII and delete Condition # 17309, Part 38 to reflect EPA's adoption of BAAQMD Regulation 8, Rules 34, and 40 into the SIP and BAAQMD's subsequent adoption of amendments to Regulation 1-523 and Regulation 8, Rule 16.
- Update Tables IV-A to include applicable NSPS subsections of 60.754, 60.756 and 60.759.
- Update Tables IV-D to include applicable NSPS subsections of 60.752.
- Revise Condition # 16462 to reflect minor wording changes made to Part 1 under application #2379.
- Revise Condition # 17309, Part 11 to update the number of transfer truck and scraper trips as modified in under application #2379
- Delete references in Condition # 17309, Parts 17 and 33 to proposed IC engines that will not be installed.
- Revise Condition # 17309, Part 20 to reflect expansion of the landfill gas collection system.
- Correct test methods referenced in Table VIII by adding optional methods and deleting obsolete methods.

X. Revision History

- [Add new terms to Section XI.](#)
- [SIP rules available on EPA's website](#)

|

XI. GLOSSARY

ACT

Federal Clean Air Act

APCO

Air Pollution Control Officer: Head of Bay Area Air Quality Management District

ARB

Air Resources Board (same as CARB)

BAAQMD

Bay Area Air Quality Management District

BACT

Best Available Control Technology

Basis

The underlying authority that allows the District to impose requirements.

CAA

The federal Clean Air Act

CAAQS

California Ambient Air Quality Standards

CAPCOA

California Air Pollution Control Officers Association

CARB

California Air Resources Board (same as ARB)

CEQA

California Environmental Quality Act

CFR

The Code of Federal Regulations. 40 CFR contains the implementing regulations for federal environmental statutes such as the Clean Air Act. Parts 50-99 of 40 CFR contain the requirements for air pollution programs.

CH₄ or CH₄

Methane

CO

Carbon Monoxide

XI. Glossary

CO2
Carbon Dioxide

CT
Combustion Zone Temperature

Cumulative Increase

The sum of permitted emissions from each new or modified source since a specified date pursuant to BAAQMD Rule 2-1-403, Permit Conditions (as amended by the District Board on 7/17/91) and SIP Rule 2-1-403, Permit Conditions (as approved by EPA on 6/23/95). Used to determine whether threshold-based requirements are triggered.

District

The Bay Area Air Quality Management District

EG
Emission Guidelines

EO
Executive Order

EPA

The federal Environmental Protection Agency.

Excluded

Not subject to any District Regulations.

Federally Enforceable, FE

All limitations and conditions which are enforceable by the Administrator of the EPA including those requirements developed pursuant to 40 CFR Part 51, subpart I (NSR), Part 52.21 (PSD), Part 60, (NSPS), Part 61, (NESHAPs), Part 63 (HAP), and Part 72 (Permits Regulation, Acid Rain), and also including limitations and conditions contained in operating permits issued under an EPA-approved program that has been incorporated into the SIP.

FP

Filterable particulate as measured by BAAQMD Method ST-15, Particulate.

H2S or H₂S
Hydrogen Sulfide

HAP

Hazardous Air Pollutant. Any pollutant listed pursuant to Section 112(b) of the Act. Also refers to the program mandated by Title I, Section 112, of the Act and implemented by ~~both~~ 40 CFR Part 63.

XI. Glossary

HHV

Higher Heating Value. The quantity of heat evolved as determined by a calorimeter where the combustion products are cooled to 60F and all water vapor is condensed to liquid.

LFG

Landfill gas

Major Facility

A facility with potential emissions of regulated air pollutants greater than or equal to 100 tons per year, greater than or equal to 10 tons per year of any single hazardous air pollutant, and/or greater than or equal to 25 tons per year of any combination of hazardous air pollutants, or such lesser quantity as determined by the EPA administrator.

MAX or Max.

Maximum

MFR

Major Facility Review. The District's term for the federal operating permit program mandated by Title V of the Federal Clean Air Act and implemented by District Regulation 2, Rule 6.

MIN or Min.

Minimum

MOP

The District's Manual of Procedures.

MSW

Municipal solid waste

MW

Molecular weight

N₂

Nitrogen

NA

Not Applicable

NAAQS

National Ambient Air Quality Standards

NESHAPs

National Emission Standards for Hazardous Air Pollutants.—~~C~~contained in 40 CFR Parts 61 and 63.

XI. Glossary

NMHC

Non-methane Hydrocarbons (same as NMOC).

NMOC

Non-methane Organic Compounds (same as NMHC).

NO_x

Oxides of nitrogen.

NSPS

Standards of Performance for New Stationary Sources. Federal standards for emissions from new stationary sources. Mandated by Title I, Section 111 of the [Federal Clean Air Act](#), and implemented by both 40 CFR Part 60 and District Regulation 10.

NSR

New Source Review. A federal program for pre-construction review and permitting of new and modified sources of air pollutants for which the District is classified "non-attainment". Mandated by Title I of the Clean Air Act and implemented by 40 CFR Parts 51 and 52 as well as District Regulation 2, Rule 2. (Note: There are additional NSR requirements mandated by the California Clean Air Act.)

O₂ or O₂ Oxygen

Offset Requirement

A New Source Review requirement to provide federally enforceable emission offsets at a specified ratio for the emissions from a new or modified source and any pre-existing cumulative increase minus any onsite contemporaneous emission reduction credits. Applies to emissions of POC, NO_x, PM₁₀, and SO₂.

Phase II Acid Rain Facility

A facility that generates electricity for sale through fossil-fuel combustion and by virtue of certain other characteristics (defined in Regulation 2, Rule 6) is subject to Titles IV and V of the Clean Air Act.

POC

Precursor Organic Compounds

PM

Total Particulate Matter

PM₁₀ or PM₁₀

Particulate matter with aerodynamic equivalent diameter of less than or equal to 10 microns

XI. Glossary

PSD

Prevention of Significant Deterioration. A federal program for permitting new and modified sources of air pollutants for which the District is classified "attainment" of the National Air Ambient Quality Standards. Mandated by Title I of the Act and implemented by both 40 CFR Part 52 and District Regulation 2, Rule 2.

PV or P/V Valve

Pressure/Vacuum Valve

RMP

Risk Management Plan

SIP

State Implementation Plan. State and District programs and regulations approved by EPA and developed in order to attain the National Air Ambient Quality Standards. Mandated by Title I of the Act.

SO₂ or SO₂

Sulfur dioxide

SSM

Startup, Shutdown, or Malfunction

SSM Plan

A plan, which states the procedures that will be followed during a startup, shutdown, or malfunction, that is prepared in accordance with the general NESHAP provisions (40 CFR Part 63, Subpart A) and maintained on site at the facility.

TAC

Toxic Air Contaminant (as identified by CARB)

THC

Total Hydrocarbons includes all NMHC plus methane (same as TOC).

Title V

Title V of the federal Clean Air Act. Requires a federally enforceable operating permit program for major and certain other facilities.

TOC

Total Organic Compounds includes all NMOC plus methane (same as THC).

TPH

Total Petroleum Hydrocarbons

XI. Glossary

TRMP

Toxic Risk Management Policy.

TRS

Total Reduced Sulfur

TSP

Total Suspended Particulate

VOC

Volatile Organic Compounds

VMT

Vehicle Miles Traveled

Symbols:

<u><</u>	<u>=</u>	<u>less than</u>
<u>></u>	<u>=</u>	<u>greater than</u>
<u><</u>	<u>=</u>	<u>less than or equal to</u>
<u>></u>	<u>=</u>	<u>greater than or equal to</u>

Units of Measure:

bhp	=	brake-horsepower
btu	=	British Thermal Unit
<u>BTU</u>	<u>=</u>	<u>British Thermal Unit</u>
<u>°C</u>	<u>=</u>	<u>degrees Centigrade</u>
<u>cfm</u>	<u>=</u>	<u>cubic feet per minute</u>
<u>dscf</u>	<u>=</u>	<u>dry standard cubic feet</u>
<u>°F</u>	<u>=</u>	<u>degrees Fahrenheit</u>
<u>ft³</u>	<u>=</u>	<u>cubic feet</u>
g	=	grams
gal	=	gallon
<u>gpm</u>	<u>=</u>	<u>gallons per minute</u>
<u>gr</u>	<u>=</u>	<u>grains</u>
hp	=	horsepower
hr	=	hour
<u>in</u>	<u>=</u>	<u>inches</u>
lb	=	pound
<u>in</u>	<u>=</u>	<u>inches</u>
<u>lb</u>	<u>=</u>	<u>pound</u>
<u>lbmol</u>	<u>=</u>	<u>pound-mole</u>
<u>max</u>	<u>=</u>	<u>maximum</u>

XI. Glossary

m ²	=	square meter
<u>m³</u>	=	<u>cubic meters</u>
<u>max</u>	=	<u>maximum</u>
min	=	minute
mm	=	million
<u>mm</u>	=	<u>millimeter</u>
<u>MM</u>	=	<u>million</u>
<u>MMBTU</u>	=	<u>million BTU</u>
<u>MMcf</u>	=	<u>million cubic feet</u>
<u>Mg</u>	=	<u>mega grams</u>
<u>ppb</u>	=	<u>parts per billion</u>
<u>ppbv</u>	=	<u>parts per billion, by volume</u>
<u>ppm</u>	=	<u>parts per million</u>
ppmv	=	parts per million, by volume
ppmw	=	parts per million, by weight
psia	=	pounds per square inch, absolute
psig	=	pounds per square inch, gauge
<u>scf</u>	=	<u>standard cubic feet</u>
scfm	=	standard cubic feet per minute
<u>sdcf</u>	=	<u>standard dry cubic feet</u>
<u>sdcfm</u>	=	<u>standard dry cubic feet per minute</u>
<u>yd</u>	=	<u>yard</u>
<u>yd³</u>	=	<u>cubic yards</u>
yr	=	year

XI.XII. APPLICABLE STATE IMPLEMENTATION PLAN

The Bay Area Air Quality Management District's portion of the State Implementation Plan can be found at EPA Region 9's website. The address is:

<http://yosemite1.epa.gov/r9/r9sips.nsf/California?ReadForm&Start=1&Count=30&Expand=3.1>

See Attachments